

Package ‘BMisc’

July 11, 2022

Title Miscellaneous Functions for Panel Data, Quantiles, and Printing Results

Version 1.4.5

Description These are miscellaneous functions for working with panel data, quantiles, and printing results. For panel data, the package includes functions for making a panel data balanced (that is, dropping missing individuals that have missing observations in any time period), converting id numbers to row numbers, and to treat repeated cross sections as panel data under the assumption of rank invariance. For quantiles, there are functions to make distribution functions from a set of data points (this is particularly useful when a distribution function is created in several steps), to combine distribution functions based on some external weights, and to invert distribution functions. Finally, there are several other miscellaneous functions for obtaining weighted means, weighted distribution functions, and weighted quantiles; to generate summary statistics and their differences for two groups; and to add or drop covariates from formulas.

Depends R (>= 3.1.0)

Imports data.table, Rcpp

License GPL-2

Suggests testthat (>= 3.0.0), plm, tibble

Encoding UTF-8

RoxygenNote 7.1.2

Config/testthat/edition 3

LinkingTo Rcpp, RcppArmadillo

URL <https://bcallaway11.github.io/BMisc/>,
<https://github.com/bcallaway11/BMisc>

BugReports <https://github.com/bcallaway11/BMisc/issues>

NeedsCompilation yes

Author Brantly Callaway [aut, cre]

Maintainer Brantly Callaway <brantly.callaway@uga.edu>

Repository CRAN

Date/Publication 2022-07-11 18:30:10 UTC

R topics documented:

| | |
|--------------------------------|-----------|
| addCovToFormla | 2 |
| blockBootSample | 3 |
| BMisc | 3 |
| checkfun | 4 |
| combineDfs | 4 |
| compareBinary | 5 |
| cs2panel | 6 |
| dropCovFromFormla | 6 |
| getListElement | 7 |
| getWeightedDf | 7 |
| getWeightedMean | 8 |
| getWeightedQuantiles | 8 |
| ids2rownum | 9 |
| invertEcdf | 10 |
| lhs.vars | 10 |
| makeBalancedPanel | 11 |
| makeDist | 11 |
| multiplier_bootstrap | 12 |
| panel2cs | 13 |
| panel2cs2 | 13 |
| rhs | 14 |
| rhs.vars | 14 |
| source_all | 15 |
| subsample | 15 |
| toformula | 16 |
| TorF | 17 |
| weighted.checkfun | 17 |
| Index | 18 |

| | |
|----------------|-------------------------------------|
| addCovToFormla | <i>Add a Covariate to a Formula</i> |
|----------------|-------------------------------------|

Description

addCovFromFormla adds some covariates to a formula; covs should be a list of variable names

Usage

```
addCovToFormla(covs, formla)
```

Arguments

| | |
|--------|------------------------------------|
| covs | should be a list of variable names |
| formla | which formula to add covariates to |

Value

formula

Examples

```
formla <- y ~ x
addCovToFormla(list("w","z"), formla)
```

```
formla <- ~x
addCovToFormla("z", formla)
```

blockBootSample *Block Bootstrap*

Description

make draws of all observations with the same id in a panel data context. This is useful for bootstrapping with panel data.

Usage

```
blockBootSample(data, idname)
```

Arguments

| | |
|--------|--------------------------------------------------------|
| data | data.frame from which you want to bootstrap |
| idname | column in data which contains an individual identifier |

Value

data.frame bootstrapped from the original dataset; this data.frame will contain new ids

Examples

```
data("LaborSupply", package="plm")
bbs <- blockBootSample(LaborSupply, "id")
nrow(bbs)
head(bbs$id)
```

BMisc *BMisc*

Description

A set of miscellaneous helper functions

| | |
|----------|-----------------------|
| checkfun | <i>Check Function</i> |
|----------|-----------------------|

Description

The check function used for optimizing to get quantiles

Usage

```
checkfun(a, tau)
```

Arguments

| | |
|-----|------------------------------------------------|
| a | vector to compute quantiles for |
| tau | between 0 and 1, ex. .5 implies get the median |

Value

numeric value

Examples

```
x <- rnorm(100)
x[which.min(checkfun(x, 0.5))] ##should be around 0
```

| | |
|------------|-------------------------------------------|
| combineDfs | <i>Combine Two Distribution Functions</i> |
|------------|-------------------------------------------|

Description

Combines two distribution functions with given weights by pstrat

Usage

```
combineDfs(y.seq, dflist, pstrat = NULL, ...)
```

Arguments

| | |
|--------|------------------------------------------------------------------------------------------------------------------------------------------------|
| y.seq | sequence of possible y values |
| dflist | list of distribution functions to combine |
| pstrat | a vector of weights to put on each distribution function; if weights are not provided then equal weight is given to each distribution function |
| ... | additional arguments that can be past to BMisc::makeDist |

Value

ecdf

Examples

```
x <- rnorm(100)
y <- rnorm(100,1,1)
Fx <- ecdf(x)
Fy <- ecdf(y)
both <- combineDfs(seq(-2,3,0.1), list(Fx,Fy))
plot(Fx, col="green")
plot(Fy, col="blue", add=TRUE)
plot(both, add=TRUE)
```

`compareBinary`*Compare Variables across Groups*

Description

`compareBinary` takes in a variable e.g. union and runs bivariate regression of x on treatment (for summary statistics)

Usage

```
compareBinary(
  x,
  on,
  dta,
  w = rep(1, nrow(dta)),
  report = c("diff", "levels", "both")
)
```

Arguments

| | |
|--------|-----------------------------------------------------------------------------------------|
| x | variables to run regression on |
| on | binary variable |
| dta | the data to use |
| w | weights |
| report | which type of report to make; diff is the difference between the two variables by group |

Value

matrix of results

| | |
|----------|-------------------------------|
| cs2panel | <i>Cross Section to Panel</i> |
|----------|-------------------------------|

Description

Turn repeated cross sections data into panel data by imposing rank invariance; does not require that the inputs have the same length

Usage

```
cs2panel(cs1, cs2, yname)
```

Arguments

| | |
|-------|-------------------------------------------------------------------------------------------|
| cs1 | data frame, the first cross section |
| cs2 | data frame, the second cross section |
| yname | the name of the variable to calculate difference for (should be the same in each dataset) |

Value

the change in outcomes over time

| | |
|--------------------|----------------------------------------|
| dropCovFromFormula | <i>Drop a Covariate from a Formula</i> |
|--------------------|----------------------------------------|

Description

dropCovFromFormula adds drops some covariates from a formula; covs should be a list of variable names

Usage

```
dropCovFromFormula(covs, formula)
```

Arguments

| | |
|---------|---------------------------------------|
| covs | should be a list of variable names |
| formula | which formula to drop covariates from |

Value

formula

Examples

```
formla <- y ~ x + w + z
dropCovFromFormla(list("w","z"), formla)

dropCovFromFormla("z", formla)
```

| | |
|----------------|--------------------------------------------------------------|
| getListElement | <i>Return Particular Element from Each Element in a List</i> |
|----------------|--------------------------------------------------------------|

Description

a function to take a list and get a particular part out of each element in the list

Usage

```
getListElement(listolists, whichone = 1)
```

Arguments

| | |
|------------|-------------------------------------------------------------|
| listolists | a list |
| whichone | which item to get out of each list (can be numeric or name) |

Value

list of all the elements 'whichone' from each list

Examples

```
len <- 100 # number elements in list
lis <- lapply(1:len, function(l) list(x=(-1), y=l^2) ) # create list
getListElement(lis, "x")[1] # should be equal to -1
getListElement(lis, 1)[1] # should be equal to -1
```

| | |
|---------------|---------------------------------------|
| getWeightedDf | <i>Weighted Distribution Function</i> |
|---------------|---------------------------------------|

Description

Get a distribution function from a vector of values after applying some weights

Usage

```
getWeightedDf(y, y.seq = NULL, weights = NULL, norm = TRUE)
```

Arguments

| | |
|----------------------|----------------------------------------------------------------------------------------------------------------------------------|
| <code>y</code> | a vector to compute the mean for |
| <code>y.seq</code> | an optional vector of values to compute the distribution function for; the default is to use all unique values of <code>y</code> |
| <code>weights</code> | the vector of weights, can be NULL, then will just return mean |
| <code>norm</code> | normalize the weights so that they have mean of 1, default is to normalize |

Value

ecdf

`getWeightedMean` *Weighted Mean*

Description

Get the mean applying some weights

Usage

```
getWeightedMean(y, weights = NULL, norm = TRUE)
```

Arguments

| | |
|----------------------|----------------------------------------------------------------------------|
| <code>y</code> | a vector to compute the mean for |
| <code>weights</code> | the vector of weights, can be NULL, then will just return mean |
| <code>norm</code> | normalize the weights so that they have mean of 1, default is to normalize |

Value

the weighted mean

`getWeightedQuantiles` *Get Weighted Quantiles*

Description

Finds multiple quantiles by repeatedly calling `getWeightedQuantile`

Usage

```
getWeightedQuantiles(tau, cvec, weights = NULL, norm = TRUE)
```


Arguments

| | |
|---------|----------------------------------------------------------------------------|
| tau | a vector of values between 0 and 1 |
| cvec | a vector to compute quantiles for |
| weights | the weights, weighted.checkfun normalizes the weights to sum to 1. |
| norm | normalize the weights so that they have mean of 1, default is to normalize |

Value

vector of quantiles

| | |
|------------|---------------------------------------------------------|
| ids2rownum | <i>Convert Vector of ids into Vector of Row Numbers</i> |
|------------|---------------------------------------------------------|

Description

ids2rownum takes a vector of ids and converts it to the right row number in the dataset; ids should be unique in the dataset that is, don't pass the function panel data with multiple same ids

Usage

```
ids2rownum(ids, data, idname)
```

Arguments

| | |
|--------|---------------|
| ids | vector of ids |
| data | data frame |
| idname | unique id |

Value

vector of row numbers

Examples

```
ids <- seq(1,1000,length.out=100)
ids <- ids[order(runif(100))]
df <- data.frame(id=ids)
ids2rownum(df$id, df, "id")
```

invertEcdf

Invert Ecdf

Description

take an ecdf object and invert it to get a step-quantile function

Usage

```
invertEcdf(df)
```

Arguments

df an ecdf object

Value

stepfun object that contains the quantiles of the df

lhs.vars

Left-hand Side Variables

Description

Take a formula and return a vector of the variables on the left hand side, it will return NULL for a one sided formula

Usage

```
lhs.vars(formla)
```

Arguments

formla a formula

Value

vector of variable names

Examples

```
ff <- yvar ~ x1 + x2  
lhs.vars(ff)
```

makeBalancedPanel *Balance a Panel Data Set*

Description

This function drops observations from data.frame that are not part of balanced panel data set.

Usage

```
makeBalancedPanel(data, idname, tname)
```

Arguments

| | |
|--------|-----------------------------|
| data | data.frame used in function |
| idname | unique id |
| tname | time period name |

Value

data.frame that is a balanced panel

Examples

```
id <- rep(seq(1,100), each = 2) ## individual ids for setting up a two period panel
t <- rep(seq(1,2),100) ## time periods
y <- rnorm(200) ## outcomes
dta <- data.frame(id=id, t=t, y=y) ## make into data frame
dta <- dta[-7,] ## drop the 7th row from the dataset (which creates an unbalanced panel)
dta <- makeBalancedPanel(dta, idname="id", tname="t")
```

makeDist *Make a Distribution Function*

Description

turn vectors of a values and their distribution function values into an ecdf. Vectors should be the same length and both increasing.

Usage

```
makeDist(
  x,
  Fx,
  sorted = FALSE,
  rearrange = FALSE,
  force01 = FALSE,
  method = "constant"
)
```

Arguments

| | |
|-----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x | vector of values |
| Fx | vector of the distribution function values |
| sorted | boolean indicating whether or not x is already sorted; computation is somewhat faster if already sorted |
| rearrange | boolean indicating whether or not should monotize distribution function |
| force01 | boolean indicating whether or not to force the values of the distribution function (i.e. Fx) to be between 0 and 1 |
| method | which method to pass to approxfun to approximate the distribution function. Default is "constant"; other possible choice is "linear". "constant" returns a step function, just like an empirical cdf; "linear" linearly interpolates between neighboring points. |

Value

ecdf

Examples

```
y <- rnorm(100)
y <- y[order(y)]
u <- runif(100)
u <- u[order(u)]
F <- makeDist(y,u)
```

multiplier_bootstrap *multiplier_bootstrap*

Description

A function that takes in an influence function (an $n \times k$ matrix) and the number of bootstrap iterations and returns a $B \times k$ matrix of bootstrap results. This function uses Rademacher weights.

Usage

```
multiplier_bootstrap(inf_func, biters)
```

Arguments

| | |
|----------|----------------------------------------------------------------------------------------------------------------------------|
| inf_func | $n \times k$ matrix of (e.g., these could be a matrix containing the influence function for different parameter estimates) |
| biters | the number of bootstrap iterations |

Value

a $B \times k$ matrix

panel2cs *Panel Data to Repeated Cross Sections*

Description

panel2cs takes a 2 period dataset and turns it into a cross sectional dataset. The data includes the change in time varying variables between the time periods. The default functionality is to keep all the variables from period 1 and add all the variables listed by name in timevars from period 2 to those.

Usage

```
panel2cs(data, timevars, idname, tname)
```

Arguments

| | |
|----------|--------------------------------------|
| data | data.frame used in function |
| timevars | vector of names of variables to keep |
| idname | unique id |
| tname | time period name |

Value

data.frame

panel2cs2 *Panel Data to Repeated Cross Sections*

Description

panel2cs2 takes a 2 period dataset and turns it into a cross sectional dataset; i.e., long to wide. This function considers a particular case where there is some outcome whose value can change over time. It returns the dataset from the first period with the outcome in the second period and the change in outcomes over time appended to it

Usage

```
panel2cs2(data, yname, idname, tname, balance_panel = TRUE)
```

Arguments

| | |
|---------------|----------------------------------------------------------------------------------------------------------------------|
| data | data.frame used in function |
| yname | name of outcome variable that can change over time |
| idname | unique id |
| tname | time period name |
| balance_panel | whether to ensure that panel is balanced. Default is TRUE, but code runs somewhat faster if this is set to be FALSE. |

Value

data from first period with .y0 (outcome in first period), .y1 (outcome in second period), and .dy (change in outcomes over time) appended to it

| | |
|-----|-----------------------------------|
| rhs | <i>Right-hand Side of Formula</i> |
|-----|-----------------------------------|

Description

Take a formula and return the right hand side of the formula

Usage

```
rhs(formla)
```

Arguments

```
formla          a formula
```

Value

a one sided formula

Examples

```
ff <- yvar ~ x1 + x2  
rhs(ff)
```

| | |
|----------|----------------------------------|
| rhs.vars | <i>Right-hand Side Variables</i> |
|----------|----------------------------------|

Description

Take a formula and return a vector of the variables on the right hand side

Usage

```
rhs.vars(formla)
```

Arguments

```
formla          a formula
```

Value

vector of variable names

Examples

```
ff <- yvar ~ x1 + x2
rhs.vars(ff)
```

```
ff <- y ~ x1 + I(x1^2)
rhs.vars(ff)
```

source_all

source_all

Description

Source all the files in a folder

Usage

```
source_all(fldr)
```

Arguments

fldr path to a folder

subsample

Subsample of Observations from Panel Data

Description

returns a subsample of a panel data set; in particular drops all observations that are not in keepids. If it is not set, randomly keeps nkeep observations.

Usage

```
subsample(dta, idname, tname, keepids = NULL, nkeep = NULL)
```

Arguments

dta a data.frame which is a balanced panel
idname the name of the id variable
tname the name of the time variable
keepids which ids to keep
nkeep how many ids to keep (only used if keepids is not set); the default is the number of unique ids

Value

a data.frame that contains a subsample of dta

Examples

```
data("LaborSupply", package="plm")
nrow(LaborSupply)
unique(LaborSupply$year)
ss <- subsample(LaborSupply, "id", "year", nkeep=100)
nrow(ss)
```

toformula

Variable Names to Formula

Description

take a name for a y variable and a vector of names for x variables and turn them into a formula

Usage

```
toformula(yname, xnames)
```

Arguments

| | |
|--------|---------------------------------|
| yname | the name of the y variable |
| xnames | vector of names for x variables |

Value

a formula

Examples

```
toformula("yvar", c("x1", "x2"))

## should return yvar ~ 1
toformula("yvar", rhs.vars(~1))
```

| | |
|------|-------------|
| TorF | <i>TorF</i> |
|------|-------------|

Description

A function to replace NA's with FALSE in vector of logicals

Usage

```
TorF(cond, use_isTRUE = FALSE)
```

Arguments

| | |
|------------|-------------------------------------------------------------------------------------------------------|
| cond | a vector of conditions to check |
| use_isTRUE | whether or not to use a vectorized version of isTRUE. This is generally slower but covers more cases. |

Value

logical vector

| | |
|-------------------|--------------------------------|
| weighted.checkfun | <i>Weighted Check Function</i> |
|-------------------|--------------------------------|

Description

Weights the check function

Usage

```
weighted.checkfun(q, cvec, tau, weights)
```

Arguments

| | |
|---------|--------------------------------------------------------------------|
| q | the value to check |
| cvec | vector of data to compute quantiles for |
| tau | between 0 and 1, ex. .5 implies get the median |
| weights | the weights, weighted.checkfun normalizes the weights to sum to 1. |

Value

numeric

Index

[addCovToFormula](#), [2](#)

[blockBootSample](#), [3](#)
[BMisc](#), [3](#)

[checkfun](#), [4](#)
[combineDfs](#), [4](#)
[compareBinary](#), [5](#)
[cs2panel](#), [6](#)

[dropCovFromFormula](#), [6](#)

[getListElement](#), [7](#)
[getWeightedDf](#), [7](#)
[getWeightedMean](#), [8](#)
[getWeightedQuantiles](#), [8](#)

[ids2rownum](#), [9](#)
[invertEcdf](#), [10](#)

[lhs.vars](#), [10](#)

[makeBalancedPanel](#), [11](#)
[makeDist](#), [11](#)
[multiplier_bootstrap](#), [12](#)

[panel2cs](#), [13](#)
[panel2cs2](#), [13](#)

[rhs](#), [14](#)
[rhs.vars](#), [14](#)

[source_all](#), [15](#)
[subsample](#), [15](#)

[toformula](#), [16](#)
[TorF](#), [17](#)

[weighted.checkfun](#), [17](#)