

Package ‘dataRetrieval’

February 18, 2022

Type Package

Title Retrieval Functions for USGS and EPA Hydrologic and Water Quality Data

Version 2.7.11

Description Collection of functions to help retrieve U.S. Geological Survey (USGS) and U.S. Environmental Protection Agency (EPA) water quality and hydrology data from web services. USGS web services are discovered from National Water Information System (NWIS) <<https://waterservices.usgs.gov/>> and <<https://waterdata.usgs.gov/nwis>>. Both EPA and USGS water quality data are obtained from the Water Quality Portal <<https://www.waterqualitydata.us/>>.

License CC0

Copyright This software is in the public domain because it contains materials that originally came from the United States Geological Survey, an agency of the United States Department of Interior.

Depends R (>= 3.5.0)

Imports httr (>= 1.0.0), curl, lubridate (>= 1.5.0), stats, utils, xml2, readr (>= 1.0.0), jsonlite

Suggests covr, dplyr, ggplot2, DT, gridExtra, knitr, rmarkdown, sf, testthat

Encoding UTF-8

BuildVignettes true

VignetteBuilder knitr

BugReports <https://github.com/USGS-R/dataRetrieval/issues>

URL <https://pubs.usgs.gov/tm/04/a10/>

RoxygenNote 7.1.2

NeedsCompilation no

Author Laura DeCicco [aut, cre] (<<https://orcid.org/0000-0002-3915-9487>>), Robert Hirsch [aut] (<<https://orcid.org/0000-0002-4534-075X>>),

David Lorenz [aut],
 Jordan Read [ctb],
 Jordan Walker [ctb],
 Lindsay Carr [ctb],
 David Watkins [aut] (<<https://orcid.org/0000-0002-7544-0700>>),
 David Blodgett [ctb],
 Mike Johnson [aut] (<<https://orcid.org/0000-0002-5288-8350>>)

Maintainer Laura DeCicco <ldecicco@usgs.gov>

Repository CRAN

Date/Publication 2022-02-18 18:20:02 UTC

R topics documented:

addWaterYear	3
calcWaterYear	4
constructNWISURL	4
constructUseURL	6
constructWQPURL	7
countyCd	8
countyCdLookup	8
dataRetrieval	9
findNLDI	9
getQuerySummary	11
getWebServiceData	12
get_nldi_sources	13
importNGWMN	13
importRDB1	14
importWaterML1	16
importWaterML2	18
importWQP	19
is_dataRetrieval_user	20
parameterCdFile	21
readNGWMNdata	21
readNGWMNlevels	22
readNGWMNsites	23
readNWISdata	24
readNWISdv	27
readNWISgwl	29
readNWISmeas	31
readNWISpCode	33
readNWISpeak	34
readNWISqw	35
readNWISrating	38
readNWISsite	39
readNWISstat	41
readNWISuse	43
readNWISuv	44

readWQPdata 46
 readWQPqw 50
 readWQPsummary 53
 renameNWISColumns 54
 setAccess 56
 stateCd 57
 stateCdLookup 58
 whatNWISdata 58
 whatNWISsites 60
 whatWQPdata 61
 whatWQPsamples 62
 zeroPad 64

Index **66**

addWaterYear *add a water year column*

Description

Add a column to the dataRetrieval data frame with the water year. WQP queries will return a water year column for the start and end dates of the data.

Usage

```
addWaterYear(rawData)
```

Arguments

rawData the daily- or unit-values dataset retrieved from NWISweb. Must have at least one of the following columns to add the new water year columns: 'dateTime', 'Date', 'ActivityStartDate', or 'ActivityEndDate'. The date column(s) can be character, POSIXct, Date. They cannot be numeric.

Value

data.frame with an additional integer column with "WY" appended to the date column name. For WQP, there will be 2 columns: 'ActivityStartDateWY' and 'ActivityEndDateWY'.

Examples

```
nwisData <- readNWISdv('04085427', '00060', '2012-01-01', '2012-06-30')
nwisData <- addWaterYear(nwisData)

wqpData <- readWQPqw('USGS-01594440', '01075', '', '')
wqpData <- addWaterYear(wqpData)
```

calcWaterYear *Extract WY from a date*

Description

Determine the correct water year based on a calendar date.

Usage

```
calcWaterYear(dateVec)
```

Arguments

dateVec vector of dates as character ("YYYY-DD-MM"), Date, or POSIXct. Numeric does not work.

Details

This function calculates a water year based on the USGS definition that a water year starts on October 1 of the year before, and ends on September 30. For example, water year 2015 started on 2014-10-01 and ended on 2015-09-30. See the USGS definition at https://water.usgs.gov/nwc/explain_data.html.

Value

numeric vector indicating the water year

Examples

```
x <- seq(as.Date("2010-01-01"), as.Date("2010-12-31"), by="month")
calcWaterYear(x)

y <- c("2010-01-01", "1994-02", "1980", "2009-11-01", NA)
calcWaterYear(y)
```

constructNWISURL *Construct NWIS url for data retrieval*

Description

Imports data from NWIS web service. This function gets the data from here: <https://nwis.waterdata.usgs.gov/nwis/qwdata> A list of parameter codes can be found here: <https://nwis.waterdata.usgs.gov/nwis/pmcodes/> A list of statistic codes can be found here: https://nwis.waterdata.usgs.gov/nwis/help/?read_file=stat&format=table

Usage

```

constructNWISURL(
  siteNumbers,
  parameterCd = "00060",
  startDate = "",
  endDate = "",
  service,
  statCd = "00003",
  format = "xml",
  expanded = TRUE,
  ratingType = "base",
  statReportType = "daily",
  statType = "mean"
)

```

Arguments

siteNumbers	string or vector of strings USGS site number. This is usually an 8 digit number
parameterCd	string or vector of USGS parameter code. This is usually an 5 digit number.
startDate	character starting date for data retrieval in the form YYYY-MM-DD. Default is "" which indicates retrieval for the earliest possible record.
endDate	character ending date for data retrieval in the form YYYY-MM-DD. Default is "" which indicates retrieval for the latest possible record.
service	string USGS service to call. Possible values are "dv" (daily values), "uv" (unit/instantaneous values), "qw" (water quality data), "gwlevels" (groundwater),and "rating" (rating curve), "peak", "meas" (discrete streamflow measurements), "stat" (statistics web service BETA).
statCd	string or vector USGS statistic code only used for daily value service. This is usually 5 digits. Daily mean (00003) is the default.
format	string, can be "tsv" or "xml", and is only applicable for daily and unit value requests. "tsv" returns results faster, but there is a possiblitiy that an incomplete file is returned without warning. XML is slower, but will offer a warning if the file was incomplete (for example, if there was a momentary problem with the internet connection). It is possible to safely use the "tsv" option, but the user must carefully check the results to see if the data returns matches what is expected. The default is therefore "xml".
expanded	logical defaults to TRUE. If TRUE, retrieves additional information, only applicable for qw data.
ratingType	can be "base", "corr", or "exsa". Only applies to rating curve data.
statReportType	character Only used for statistics service requests. Time division for statistics: daily, monthly, or annual. Default is daily. Note that daily provides statistics for each calendar day over the specified range of water years, i.e. no more than 366 data points will be returned for each site/parameter. Use readNWISdata or readNWISdv for daily averages. Also note that 'annual' returns statistics for the calendar year. Use readNWISdata for water years. Monthly and yearly provide statistics for each month and year within the range individually.

statType character Only used for statistics service requests. Type(s) of statistics to output for daily values. Default is mean, which is the only option for monthly and yearly report types. See the statistics service documentation at <https://waterservices.usgs.gov/rest/Statistics-Service.html> for a full list of codes.

Value

url string

Examples

```
site_id <- '01594440'
startDate <- '1985-01-01'
endDate <- ''
pCode <- c("00060", "00010")
url_daily <- constructNWISURL(site_id, pCode,
                             startDate, endDate, 'dv', statCd=c("00003", "00001"))
url_unit <- constructNWISURL(site_id, pCode, "2012-06-28", "2012-06-30", 'iv')

url_qw_single <- constructNWISURL(site_id, "01075", startDate, endDate, 'qw')
url_qw <- constructNWISURL(site_id, c('01075', '00029', '00453'),
                           startDate, endDate, 'qw')
url_daily_tsv <- constructNWISURL(site_id, pCode, startDate, endDate, 'dv',
                                  statCd=c("00003", "00001"), format="tsv")
url_rating <- constructNWISURL(site_id, service="rating", ratingType="base")
url_peak <- constructNWISURL(site_id, service="peak")
url_meas <- constructNWISURL(site_id, service="meas")
urlQW <- constructNWISURL("450456092225801", "70300", startDate="", endDate="", "qw", expanded=TRUE)
```

constructUseURL

Construct URL for NWIS water use data service

Description

Reconstructs URLs to retrieve data from here: <https://waterdata.usgs.gov/nwis/wu>

Usage

```
constructUseURL(years, stateCd, countyCd, categories)
```

Arguments

years integer Years for data retrieval. Must be years ending in 0 or 5, or "ALL", which retrieves all available years.

stateCd could be character (full name, abbreviation, id), or numeric (id)

countyCd could be numeric (County IDs from countyCdLookup) or character ("ALL")

categories character Two-letter category abbreviation(s)

Value

url string

Examples

```
url <- constructUseURL(years=c(1990,1995),stateCd="Ohio",countyCd = c(1,3), categories = "ALL")
```

constructWQPURL	<i>Construct WQP url for data retrieval</i>
-----------------	---

Description

Construct WQP url for data retrieval. This function gets the data from here: <https://www.waterqualitydata.us>

Usage

```
constructWQPURL(siteNumbers, parameterCd, startDate, endDate, zip = TRUE)
```

Arguments

siteNumbers	string or vector of strings USGS site number. This is usually an 8 digit number
parameterCd	string or vector of USGS parameter code. This is usually an 5 digit number.
startDate	character starting date for data retrieval in the form YYYY-MM-DD. Default is "" which indicates retrieval for the earliest possible record.
endDate	character ending date for data retrieval in the form YYYY-MM-DD. Default is "" which indicates retrieval for the latest possible record.
zip	logical to request data via downloading zip file. Default set to TRUE.

Value

url string

Examples

```
site_id <- '01594440'
startDate <- '1985-01-01'
endDate <- ''
pCode <- c("00060","00010")
url_wqp <- constructWQPURL(paste("USGS",site_id,sep="-"),
                          c('01075','00029','00453'),
                          startDate,endDate)
url_wqp
charNames <- c("Temperature",
              "Temperature, sample",
              "Temperature, water",
```

```

      "Temperature, water, deg F")
obs_url_orig <- constructWQPURL(siteNumbers = c("IIDFG-41WSSPAHS",
      "USGS-02352560"),
      parameterCd = charNames,
      startDate,"")

obs_url_orig

```

countyCd *US County Code Lookup Table*

Description

Data originally pulled from https://www2.census.gov/geo/docs/reference/codes/files/national_county.txt on April 1, 2015. On Feb. 11, 2022, the fields were updated with the file found in inst/extdata, which is used internally with NWIS retrievals.

Value

countyCd data frame.

Name	Type	Description
STUSAB	character	State abbreviation
STATE	character	two-digit ANSI code
COUNTY	character	three-digit county code
COUNTY_NAME	character	County full name
COUNTY_ID	character	County id

Examples

```
head(countyCd)
```

countyCdLookup *County code look up*

Description

Function to simplify finding county and county code definitions. Used in readNWISdata and readNWISuse.

Usage

```
countyCdLookup(state, county, outputType = "id")
```


Arguments

state could be character (full name, abbreviation, id), or numeric (id)
 county could be character (name, with or without "County") or numeric (id)
 outputType character can be "fullName", "tableIndex", "id", or "fullEntry".

Examples

```
id <- countyCdLookup(state = "WI", county = "Dane")
name <- countyCdLookup(state = "OH", county = 13, output = "fullName")
index <- countyCdLookup(state = "Pennsylvania", county = "ALLEGHENY COUNTY", output = "tableIndex")
fromIDs <- countyCdLookup(state = 13, county = 5, output = "fullName")
already_correct <- countyCdLookup(county = "51001")
```

dataRetrieval *Retrieval functions for USGS and EPA data*

Description

Package: dataRetrieval
 Type: Package
 License: Unlimited for this package, dependencies have more restrictive licensing.
 Copyright: This software is in the public domain because it contains materials that originally came from the United States G
 LazyLoad: yes

Details

Retrieval functions for USGS and EPA hydrologic and water quality data.
 Please see <https://pubs.er.usgs.gov/publication/tm4A10> for more information.

Author(s)

Laura De Cicco <ldecicco@usgs.gov>

findNLDI *R Client for the Network Linked Data Index*

Description

Provides a formal client to the USGS [Network Linked Data Index](#).

Usage

```
findNLDI(
  comid = NULL,
  nwis = NULL,
  wqp = NULL,
  huc12 = NULL,
  location = NULL,
  origin = NULL,
  nav = NULL,
  find = c("flowlines"),
  distance_km = 100,
  no_sf = FALSE
)
```

Arguments

comid	numeric or character. An NHDPlusV2 COMID
nwis	numeric or character. A USGS NWIS surface water siteID
wqp	numeric or character. A water quality point ID
huc12	numeric or character. A WBD HUC12 unit ID
location	numeric vector. Coordinate pair in WGS84 SRS ordered lng/lat (X,Y)
origin	named list. Specifying a feature type and ID (e.g. list("comid" = 101))
nav	character vector. where to navigate from the starting point. Options include along the upper mainsteam (UM), upstream tributary (UT), downstream mainstem (DM) and downstream divergences (DD). You may select one or more of the abbreviations ("UM", "UT", "DM", "DD").
find	character vector. Define what resources to find along the navigation path(s) (see <code>get_nldi_sources()</code> \$source). Can also include 'basin' or 'flowline', which will return the upstream basin of the starting feature or flowlines along the navigation respectively. The default is "flowlines". If you provide any other resource, AND want flowlines, then flowlines must be explicitly requested.
distance_km	numeric. Define how far to look along the navigation path in kilometers (default = 100)
no_sf	if available, should 'sf' be used for parsing, defaults to 'TRUE' if 'sf' is locally installed

Details

The function is useful for topology and location based feature discovery. A user must specify an origin feature, optional navigation direction(s) along the network, as well as features to identify along the navigated paths. Valid starting options can be given by one of the following arguments: comid, nwis, huc12, wqp, location, and start.

Value

a list of data.frames if sf is not installed, a list of sf objects if it is

Examples

```

# Find Features / Define origin features

## Find feature by COMID
findNLDI(comid = 101)

## Find feature by NWIS ID
findNLDI(nwis = '11120000')

## Find feature by WQP ID
findNLDI(wqp = 'USGS-04024315')

## Find feature by LOCATION
findNLDI(location = c(-115,40))

## GENERAL ORIGIN: COMID
findNLDI(origin = list("comid" = 101))

## GENERAL ORIGIN: WaDE
findNLDI(origin = list("wade" = 'CA_45206'))

# Navigation (flowlines will be returned if find is unspecified)
# UPPER MAINSTEM of USGS-11120000
findNLDI(nwis = '11120000', nav = "UM")

# MULTI-REQUEST
# UPPER MAINSTEM and TRIBUTARY of USGS-11120000
findNLDI(nwis = '11120000', nav = c("UT", "UM"))

# Discover Features(flowlines will not be returned unless included in find)

## Find feature(s) on the upper tributary of USGS-11120000
findNLDI(nwis = '11120000', nav = "UT", find = c("nwis", "wqp"))

## Find upstream basin boundary and of USGS-11120000
findNLDI(nwis = '11120000', find = "basin")

# Control Distance
## Limit search to 50 km
findNLDI(comid = 101, nav = "DM", find = c("nwis", "wqp", "flowlines"), distance_km = 50)

```

getQuerySummary

getting header information from a WQP query

Description

getting header information from a WQP query

Usage

```
getQuerySummary(url)
```

Arguments

url the query url

getWebServiceData *Function to return data from web services*

Description

This function accepts a url parameter, and returns the raw data. The function enhances [GET](#) with more informative error messages.

Usage

```
getWebServiceData(obs_url, ...)
```

Arguments

obs_url character containing the url for the retrieval
... information to pass to header request

Value

raw data from web services

Examples

```
siteNumber <- "02177000"  
startDate <- "2012-09-01"  
endDate <- "2012-10-01"  
offering <- '00003'  
property <- '00060'  
obs_url <- constructNWISURL(siteNumber,property,startDate,endDate,'dv')  
  
rawData <- getWebServiceData(obs_url)
```

get_nldi_sources	<i>Get current NLDI offerings</i>
------------------	-----------------------------------

Description

Used to query the current resources available through the NLDI

Usage

```
get_nldi_sources()
```

Value

data.frame

Examples

```
get_nldi_sources()
```

importNGWMN	<i>Function to return data from the National Ground Water Monitoring Network waterML2 format</i>
-------------	--

Description

This function accepts a url parameter for a WaterML2 getObservation. This function is still under development, but the general functionality is correct.

Usage

```
importNGWMN(input, asDateTime = FALSE, tz = "UTC")
```

Arguments

input	character or raw, containing the url for the retrieval or a path to the data file, or raw XML.
asDateTime	logical, if TRUE returns date and time as POSIXct, if FALSE, character
tz	character to set timezone attribute of dateTime. Default is "UTC", and converts the date times to UTC, properly accounting for daylight savings times based on the data's provided time zone offset. Possible values to provide are "America/New_York", "America/Chicago", "America/Denver", "America/Los_Angeles", "America/Anchorage", as well as the following which do not use daylight savings time: "America/Honolulu", "America/Jamaica", "America/Managua", "America/Phoenix", and "America/Metlakatla". See also OlsonNames() for more information on time zones.

Value

mergedDF a data frame source, time, value, uom, uomTitle, comment, gmlID

Examples

```
obs_url <- paste("https://cida.usgs.gov/ngwmn_cache/sos?request=GetObservation",
"service=SOS", "version=2.0.0",
"observedProperty=urn:ogc:def:property:OGC:GroundWaterLevel",
"responseFormat=text/xml",
"featureOfInterest=VW_GWDP_GEOSEVER.USGS.403836085374401", sep="&")

data_returned <- importNGWMN(obs_url)
```

importRDB1

Function to return data from the NWIS RDB 1.0 format

Description

This function accepts a url parameter that already contains the desired NWIS site, parameter code, statistic, startdate and enddate. It is not recommended to use the RDB format for importing multi-site data.

Usage

```
importRDB1(obs_url, asDateTime = TRUE, convertType = TRUE, tz = "UTC")
```

Arguments

obs_url	character containing the url for the retrieval or a file path to the data file.
asDateTime	logical, if TRUE returns date and time as POSIXct, if FALSE, Date
convertType	logical, defaults to TRUE. If TRUE, the function will convert the data to dates, datetimes, numerics based on a standard algorithm. If false, everything is returned as a character
tz	character to set timezone attribute of datetime. Default converts the datetimes to UTC (properly accounting for daylight savings times based on the data's provided tz_cd column). Recommended US values include "UTC", "America/New_York", "America/Chicago", "America/Denver", "America/Los_Angeles", "America/Anchorage", "America/Honolulu", "America/Jamaica", and "America/Metlakatla". For a complete list, see https://en.wikipedia.org/wiki/List_of_tz_database_time_zones

Value

A data frame with the following columns:

Name	Type	Description
agency_cd	character	The NWIS code for the agency reporting the data
site_no	character	The USGS site number
datetime	POSIXct character	The date and time of the value converted to UTC (if asDateTime = TRUE) or raw character string (if asDateTime = FALSE)
tz_cd	character	The time zone code for datetime
code	character	Any codes that qualify the corresponding value
value	numeric	The numeric value for the parameter
tz_cd_reported	The originally reported time zone	

Note that code and value are repeated for the parameters requested. The names are of the form XD_P_S, where X is literal, D is an option description of the parameter, P is the parameter code, and S is the statistic code (if applicable). If a date/time (dt) column contained incomplete date and times, a new column of dates and time was inserted. This could happen when older data was reported as dates, and newer data was reported as a date/time.

There are also several useful attributes attached to the data frame:

Name	Type	Description
url	character	The url used to generate the data
queryTime	POSIXct	The time the data was returned
comment	character	Header comments from the RDB file

Examples

```

site_id <- "02177000"
startDate <- "2012-09-01"
endDate <- "2012-10-01"
offering <- "00003"
property <- "00060"

obs_url <- constructNWISURL(site_id,property,
                             startDate,endDate,"dv",format="tsv")

data <- importRDB1(obs_url)

urlMultiPcodes <- constructNWISURL("04085427",c("00060","00010"),
                                   startDate,endDate,"dv",statCd=c("00003","00001"),"tsv")

multiData <- importRDB1(urlMultiPcodes)

unitDataURL <- constructNWISURL(site_id,property,
                                "2020-10-30","2020-11-01","uv",format="tsv") #includes timezone switch

unitData <- importRDB1(unitDataURL, asDateTime=TRUE)

qwURL <- constructNWISURL(c('04024430','04024000'),

```

```

      c('34247','30234','32104','34220'),
      "2010-11-03", "", "qw", format="rdb")

qwData <- importRDB1(qwURL, asDateTime=TRUE, tz="America/Chicago")

iceSite <- '04024000'
start <- "2015-11-09"
end <- "2015-11-24"
urlIce <- constructNWISURL(iceSite,"00060",start, end,"uv",format="tsv")

ice <- importRDB1(urlIce, asDateTime=TRUE)
iceNoConvert <- importRDB1(urlIce, convertType=FALSE)

# User file:
filePath <- system.file("extdata", package="dataRetrieval")
fileName <- "RDB1Example.txt"
fullPath <- file.path(filePath, fileName)
importUserRDB <- importRDB1(fullPath)

```

importWaterML1

Function to return data from the NWISWeb WaterML1.1 service

Description

This function accepts a url parameter that already contains the desired NWIS site, parameter code, statistic, startdate and enddate.

Usage

```
importWaterML1(obs_url, asDateTime = FALSE, tz = "UTC")
```

Arguments

obs_url	character or raw, containing the url for the retrieval or a file path to the data file, or raw XML.
asDateTime	logical, if TRUE returns date and time as POSIXct, if FALSE, Date
tz	character to set timezone attribute of datetime. Default converts the datetimes to UTC (properly accounting for daylight savings times based on the data's provided tz_cd column). Recommended US values include "UTC", "America/New_York", "America/Chicago", "America/Denver", "America/Los_Angeles", "America/Anchorage", "America/Honolulu", "America/Jamaica" and "America/Metlakatla". For a complete list, see https://en.wikipedia.org/wiki/List_of_tz_database_time_zones

Value

A data frame with the following columns:

Name	Type	Description
agency_cd	character	The NWIS code for the agency reporting the data
site_no	character	The USGS site number
	POSIXct	The date and time of the value converted to UTC (if asDateTime = TRUE),
	character	or raw character string (if asDateTime = FALSE)
tz_cd	character	The time zone code for
code	character	Any codes that qualify the corresponding value
value	numeric	The numeric value for the parameter

Note that code and value are repeated for the parameters requested. The names are of the form X_D_P_S, where X is literal, D is an option description of the parameter, P is the parameter code, and S is the statistic code (if applicable).

There are also several useful attributes attached to the data frame:

Name	Type	Description
url	character	The url used to generate the data
siteInfo	data.frame	A data frame containing information on the requested sites
variableInfo	data.frame	A data frame containing information on the requested parameters
statisticInfo	data.frame	A data frame containing information on the requested statistics on the data
queryTime	POSIXct	The time the data was returned

See Also

[renameNWISColumns](#)

Examples

```

site_id <- "02177000"
startDate <- "2012-09-01"
endDate <- "2012-10-01"
offering <- '00003'
property <- '00060'
obs_url <- constructNWISURL(site_id,property,startDate,endDate,'dv')

data <- importWaterML1(obs_url, asDateTime=TRUE)

groundWaterSite <- "431049071324301"
startGW <- "2013-10-01"
endGW <- "2014-06-30"
groundwaterExampleURL <- constructNWISURL(groundWaterSite, NA,
  startGW,endGW, service="gwlevels")
groundWater <- importWaterML1(groundwaterExampleURL)
groundWater2 <- importWaterML1(groundwaterExampleURL, asDateTime=TRUE)

unitDataURL <- constructNWISURL(site_id,property,
  "2013-11-03","2013-11-03",'uv')
unitData <- importWaterML1(unitDataURL,TRUE)

```

```

# Two sites, two pcodes, one site has two data descriptors:
siteNumber <- c('01480015','04085427')
obs_url <- constructNWISURL(siteNumber,c("00060","00010"),startDate,endDate,'dv')
data <- importWaterML1(obs_url)
data$dateTime <- as.Date(data$dateTime)
data <- renameNWISColumns(data)
names(attributes(data))
attr(data, "url")
attr(data, "disclaimer")

inactiveSite <- "05212700"
inactiveSite <- constructNWISURL(inactiveSite, "00060", "2014-01-01", "2014-01-10",'dv')
inactiveSite <- importWaterML1(inactiveSite)

inactiveAndAcitive <- c("07334200","05212700")
inactiveAndAcitive <- constructNWISURL(inactiveAndAcitive, "00060", "2014-01-01", "2014-01-10",'dv')
inactiveAndAcitive <- importWaterML1(inactiveAndAcitive)

# Timezone change with specified local timezone:
tzURL <- constructNWISURL("04027000", c("00300","63680"), "2011-11-05", "2011-11-07","uv")
tzIssue <- importWaterML1(tzURL,
                          asDateTime = TRUE, tz = "America/Chicago")

# raw XML
url <- constructNWISURL(service = 'dv', siteNumber = '02319300', parameterCd = "00060",
                       startDate = "2014-01-01", endDate = "2014-01-01")
raw <- httr::content(httr::GET(url), as = 'raw')
rawParsed <- importWaterML1(raw)

filePath <- system.file("extdata", package="dataRetrieval")
fileName <- "WaterML1Example.xml"
fullPath <- file.path(filePath, fileName)
importFile <- importWaterML1(fullPath,TRUE)

```

importWaterML2

Parse the WaterML2 timeseries portion of a waterML2 file

Description

Returns data frame columns of all information with each time series measurement; Anything defined as a default, is returned as an attribute of that data frame.

Usage

```
importWaterML2(input, asDateTime = FALSE, tz = "UTC")
```

Arguments

input	XML with only the wml2:MeasurementTimeseries node and children
asDateTime	logical, if TRUE returns date and time as POSIXct, if FALSE, character
tz	character to set timezone attribute of datetime. Default is an empty quote, which converts the datetimes to UTC (properly accounting for daylight savings times based on the data's provided time zone offset). Possible values are "America/New_York", "America/Chicago", "America/Denver", "America/Los_Angeles", "America/Anchorage", "America/Honolulu", "America/Jamaica", "America/Managua", "America/Phoenix" and "America/Metlakatla"

Examples

```
baseURL <- "https://waterservices.usgs.gov/nwis/dv/?format=waterml,2.0"
URL <- paste(baseURL, "sites=01646500",
            "startDT=2014-09-01",
            "endDT=2014-09-08",
            "statCd=00003",
            "parameterCd=00060", sep="&")

timeseries <- importWaterML2(URL, asDateTime=TRUE, tz="UTC")
```

importWQP

Basic Water Quality Portal Data parser

Description

Imports data from the Water Quality Portal based on a specified url.

Usage

```
importWQP(obs_url, zip = TRUE, tz = "UTC", csv = FALSE)
```

Arguments

obs_url	character URL to Water Quality Portal# @keywords data import USGS web service
zip	logical to request data via downloading zip file. Default set to TRUE.
tz	character to set timezone attribute of datetime. Default is UTC (properly accounting for daylight savings times based on the data's provided tz_cd column). Possible values include "America/New_York", "America/Chicago", "America/Denver", "America/Los_Angeles", "America/Anchorage", "America/Honolulu", "America/Jamaica", "America/Managua", "America/Phoenix" and "America/Metlakatla"

csv logical. Is the data coming back with a csv or tsv format. Default is FALSE. Currently, the summary service does not support tsv, for other services tsv is the safer choice.

Value

retval dataframe raw data returned from the Water Quality Portal. Additionally, a POSIXct dateTime column is supplied for start and end times, and converted to UTC. See https://www.waterqualitydata.us/portal_userguide/ for more information.

See Also

[readWQPdata](#), [readWQPqw](#), [whatWQPsites](#)

Examples

```
# These examples require an internet connection to run
## Examples take longer than 5 seconds:
rawSampleURL <- constructWQPURL('USGS-01594440','01075', '', '')
rawSample <- importWQP(rawSampleURL)
rawSampleURL_NoZip <- constructWQPURL('USGS-01594440','01075', '', '', zip=FALSE)
rawSample2 <- importWQP(rawSampleURL_NoZip, zip=FALSE)
STORETex <- constructWQPURL('WIDNR_WQX-10032762','Specific conductance', '', '')
STORETdata <- importWQP(STORETex)
```

is_dataRetrieval_user *Is this a dataRetrieval user*

Description

Reveals if this is a user or not

Usage

```
is_dataRetrieval_user()
```

Examples

```
is_dataRetrieval_user()
```

parameterCdFile *List of USGS parameter codes*

Description

Complete list of USGS parameter codes as of Dec. 20, 2021.

Value

parameterData data frame with information about USGS parameters.

Name	Type	Description
parameter_cd	character	5-digit USGS parameter code
parameter_group_nm	character	USGS parameter group name
parameter_nm	character	USGS parameter name
casrn	character	Chemical Abstracts Service (CAS) Registry Number
srsname	character	Substance Registry Services Name
parameter_units	character	Parameter units

Examples

```
head(parameterCdFile[,1:2])
```

readNGWMNdata *import data from the National Groundwater Monitoring Network*
<https://cida.usgs.gov/ngwmn/>

Description

Only water level data and site locations and names are currently available through the web service.

Usage

```
readNGWMNdata(service, ..., asDateTime = TRUE, tz = "UTC")
```

Arguments

service	char Service for the request - "observation" and "featureOfInterest" are implemented.
...	Other parameters to supply, namely siteNumbers or bbox
asDateTime	logical if TRUE, will convert times to POSIXct format. Currently defaults to FALSE since time zone information is not included.

`tz` character to set timezone attribute of `dateTime`. Default is "UTC", and converts the date times to UTC, properly accounting for daylight savings times based on the data's provided time zone offset. Possible values to provide are "America/New_York", "America/Chicago", "America/Denver", "America/Los_Angeles", "America/Anchorage", as well as the following which do not use daylight savings time: "America/Honolulu", "America/Jamaica", "America/Managua", "America/Phoenix", and "America/Metlakatla". See also `OlsonNames()` for more information on time zones.

Examples

```
#one site
site <- "USGS.430427089284901"
# oneSite <- readNGWMNdata(siteNumbers = site, service = "observation")

#multiple sites
sites <- c("USGS.272838082142201", "USGS.404159100494601", "USGS.401216080362703")
# Very slow:
# multiSiteData <- readNGWMNdata(siteNumbers = sites, service = "observation")
# attributes(multiSiteData)

#non-USGS site
#accepts colon or period between agency and ID
site <- "MBMG:702934"
# data <- readNGWMNdata(siteNumbers = site, service = "featureOfInterest")

#site with no data returns empty data frame
noDataSite <- "UTGS.401544112060301"
# noDataSite <- readNGWMNdata(siteNumbers = noDataSite, service = "observation")

#bounding box
#bboxSites <- readNGWMNdata(service = "featureOfInterest", bbox = c(30, -102, 31, 99))
#retrieve sites. Set asDateTime to false since one site has an invalid date
# Very slow:
#bboxData <- readNGWMNdata(service = "observation", siteNumbers = bboxSites$site[1:3],
#asDateTime = FALSE)
```

readNGWMNlevels	<i>Retrieve groundwater levels from the National Ground Water Monitoring Network https://cida.usgs.gov/ngwmn/.</i>
-----------------	---

Description

Retrieve groundwater levels from the National Ground Water Monitoring Network <https://cida.usgs.gov/ngwmn/>.

Usage

```
readNGWMNlevels(siteNumbers, asDateTime = TRUE, tz = "UTC")
```

Arguments

siteNumbers	character Vector of feature IDs formatted with agency code and site number separated by a period or semicolon, e.g. USGS.404159100494601.
asDateTime	logical Should dates and times be converted to date/time objects, or returned as character? Defaults to TRUE. Must be set to FALSE if a site contains non-standard dates.
tz	character to set timezone attribute of dateTime. Default is "UTC", and converts the date times to UTC, properly accounting for daylight savings times based on the data's provided time zone offset. Possible values to provide are "America/New_York", "America/Chicago", "America/Denver", "America/Los_Angeles", "America/Anchorage", as well as the following which do not use daylight savings time: "America/Honolulu", "America/Jamaica", "America/Managua", "America/Phoenix", and "America/Metlakatla". See also OlsonNames() for more information on time zones.

Examples

```
#one site
site <- "USGS.430427089284901"
#oneSite <- readNGWMNlevels(siteNumbers = site)

#multiple sites
sites <- c("USGS:272838082142201", "USGS:404159100494601", "USGS:401216080362703")
#multiSiteData <- readNGWMNlevels(sites)

#non-USGS site
site <- "MBMG.103306"
#data <- readNGWMNlevels(siteNumbers = site, asDateTime = FALSE)

#site with no data returns empty data frame
noDataSite <- "UTGS.401544112060301"
#noDataSite <- readNGWMNlevels(siteNumbers = noDataSite)
```

readNGWMNsites	<i>Retrieve site data from the National Ground Water Monitoring Network</i> https://cida.usgs.gov/ngwmn/ .
----------------	---

Description

Retrieve site data from the National Ground Water Monitoring Network <https://cida.usgs.gov/ngwmn/>.

Usage

```
readNGWMNsites(siteNumbers)
```

Arguments

siteNumbers character Vector of feature IDs formatted with agency code and site number separated by a period or semicolon, e.g. USGS.404159100494601.

Value

A data frame the following columns: #'

Name	Type	Description
site	char	Site FID
description	char	Site description
dec_lat_va, dec_lon_va	numeric	Site latitude and longitude

Examples

```
#one site
site <- "USGS.430427089284901"
oneSite <- readNGWMNsites(siteNumbers = site)

#non-USGS site
site <- "MBMG.103306"
siteInfo <- readNGWMNsites(siteNumbers = site)
```

readNWISdata

General Data Import from NWIS

Description

Returns data from the NWIS web service. Arguments to the function should be based on <https://waterservices.usgs.gov> service calls. See examples below for ideas of constructing queries.

Usage

```
readNWISdata(..., asDateTime = TRUE, convertType = TRUE, tz = "UTC")
```

Arguments

... see <https://waterservices.usgs.gov/rest/Site-Service.html> for a complete list of options. A list of arguments can also be supplied. One important argument to include is 'service'. Possible values are "iv" (for instantaneous), "iv_recent" (for instantaneous values within the last 120 days), "dv"

(for daily values), "gwlevels" (for groundwater levels), "site" (for site service), "qw" (water-quality), "measurement", and "stat" (for statistics service). Note: "qw" and "measurement" calls go to: <https://nwis.waterdata.usgs.gov/usa/nwis> for data requests, and use different call requests schemes. The statistics service has a limited selection of arguments (see <https://waterservices.usgs.gov/rest/Statistics-Service-Test-Tool.html>).

asDateTime	logical, if TRUE returns date and time as POSIXct, if FALSE, Date
convertType	logical, defaults to TRUE. If TRUE, the function will convert the data to dates, datetimes, numerics based on a standard algorithm. If false, everything is returned as a character
tz	character to set timezone attribute of dateTime. Default is "UTC", and converts the date times to UTC, properly accounting for daylight savings times based on the data's provided tz_cd column. Possible values to provide are "America/New_York", "America/Chicago", "America/Denver", "America/Los_Angeles", "America/Anchorage", as well as the following which do not use daylight savings time: "America/Honolulu", "America/Jamaica", "America/Managua", "America/Phoenix", and "America/Metlakatla". See also OlsonNames() for more information on time zones.

Value

A data frame with the following columns:

Name	Type	Description
agency	character	The NWIS code for the agency reporting the data
site	character	The USGS site number
dateTime	POSIXct	The date and time (if applicable) of the measurement, converted to UTC for unit value data. R only al
tz_cd	character	The time zone code for dateTime column
code	character	Any codes that qualify the corresponding value
value	numeric	The numeric value for the parameter

Note that code and value are repeated for the parameters requested. The names are of the form X_D_P_S, where X is literal, D is an option description of the parameter, P is the parameter code, and S is the statistic code (if applicable).

There are also several useful attributes attached to the data frame:

Name	Type	Description
url	character	The url used to generate the data
siteInfo	data.frame	A data frame containing information on the requested sites
variableInfo	data.frame	A data frame containing information on the requested parameters
statisticInfo	data.frame	A data frame containing information on the requested statistics on the data
queryTime	POSIXct	The time the data was returned

See Also

[renameNWISColumns](#), [importWaterML1](#), [importRDB1](#)

Examples

```
# Examples not run for time considerations

dataTemp <- readNWISdata(stateCd="OH",parameterCd="00010", service="dv")
instFlow <- readNWISdata(sites="05114000", service="iv",
  parameterCd="00060",
  startDate="2014-05-01T00:00Z",endDate="2014-05-01T12:00Z")

instFlowCDT <- readNWISdata(sites="05114000", service="iv",
  parameterCd="00060",
  startDate="2014-05-01T00:00",endDate="2014-05-01T12:00",
  tz="America/Chicago")

#Empty:
multiSite <- readNWISdata(sites=c("04025000","04072150"), service="iv",
  parameterCd="00010")

#Not empty:
multiSite <- readNWISdata(sites=c("04025500","040263491"),
  service="iv", parameterCd="00060")
bBoxEx <- readNWISdata(bBox=c(-83,36.5,-81,38.5), parameterCd="00010")

startDate <- as.Date("2013-10-01")
endDate <- as.Date("2014-09-30")
waterYear <- readNWISdata(bBox=c(-83,36.5,-82.5,36.75), parameterCd="00010",
  service="dv", startDate=startDate, endDate=endDate)
siteInfo <- readNWISdata(stateCd="WI", parameterCd="00010",
  hasDataTypeCd="iv", service="site")
temp <- readNWISdata(bBox=c(-83,36.5,-82.5,36.75), parameterCd="00010", service="site",
  seriesCatalogOutput=TRUE)
wiGWL <- readNWISdata(stateCd = "WI", service = "gwlevels")
meas <- readNWISdata(state_cd = "WI", service = "measurements",
  format = "rdb_expanded")

waterYearStat <- readNWISdata(site = c("01646500"),
  service = "stat",
  statReportType="annual",
  statYearType = "water",
  missingData = "on")
monthlyStat <- readNWISdata(site=c("01646500"),
  service="stat",
  statReportType="monthly")

dailyStat <- readNWISdata(site = c("01646500"),
  service = "stat",
  statReportType = "daily",
  statType = c("p25","p50","p75","min","max"),
```

```

        parameterCd = "00060")

arg.list <- list(site = "03111548",
               statReportType = "daily",
               statType = c("p25", "p50", "p75", "min", "max"),
               parameterCd = "00060")
allDailyStats_2 <- readNWISdata(arg.list, service="stat")

#' # use county names to get data
dailyStaffordVA <- readNWISdata(stateCd = "Virginia",
                               countyCd="Stafford",
                               parameterCd = "00060",
                               startDate = "2015-01-01",
                               endDate = "2015-01-30")
va_counties <- c("51001", "51003", "51005", "51007", "51009", "51011", "51013", "51015")
va_counties_data <- readNWISdata(startDate = "2015-01-01", endDate = "2015-12-31",
                                parameterCd = "00060", countycode = va_counties)

site_id <- '01594440'
rating_curve <- readNWISdata(service = "rating", site_no = site_id, file_type="base")
all_sites_base <- readNWISdata(service = "rating", file_type="base")
all_sites_core <- readNWISdata(service = "rating", file_type="corr")
all_sites_exsa <- readNWISdata(service = "rating", file_type="exsa")
all_sites_24hrs <- readNWISdata(service = "rating", file_type="exsa", period = 24)

peak_data <- readNWISdata(service = "peak",
                          site_no = c("01594440", "040851325"),
                          range_selection = "data_range")

```

readNWISdv

Daily Value USGS NWIS Data Retrieval

Description

Imports data from NWIS web service. This function gets the data from here: <https://waterservices.usgs.gov/>

Usage

```

readNWISdv(
  siteNumbers,
  parameterCd,
  startDate = "",
  endDate = "",
  statCd = "00003"
)

```

Arguments

siteNumbers	character	USGS site number. This is usually an 8 digit number. Multiple sites can be requested with a character vector.
parameterCd	character	of USGS parameter code(s). This is usually an 5 digit number.
startDate	character	starting date for data retrieval in the form YYYY-MM-DD. Default is "" which indicates retrieval for the earliest possible record. Date arguments are always specified in local time.
endDate	character	ending date for data retrieval in the form YYYY-MM-DD. Default is "" which indicates retrieval for the latest possible record. Date arguments are always specified in local time.
statCd	character	USGS statistic code. This is usually 5 digits. Daily mean (00003) is the default.

Value

A data frame with the following columns:

Name	Type	Description
agency	character	The NWIS code for the agency reporting the data
site	character	The USGS site number
Date	Date	The date of the value
code	character	Any codes that qualify the corresponding value
value	numeric	The numeric value for the parameter

Note that code and value are repeated for the parameters requested. The names are of the form X_D_P_S, where X is literal, D is an option description of the parameter, P is the parameter code, and S is the statistic code (if applicable).

There are also several useful attributes attached to the data frame:

Name	Type	Description
url	character	The url used to generate the data
siteInfo	data.frame	A data frame containing information on the requested sites
variableInfo	data.frame	A data frame containing information on the requested parameters
statisticInfo	data.frame	A data frame containing information on the requested statistics on the data
queryTime	POSIXct	The time the data was returned

See Also

[renameNWISColumns](#), [importWaterML1](#)

Examples

```
site_id <- '04085427'
startDate <- '2012-01-01'
```

```

endDate <- '2012-06-30'
pCode <- '00060'

rawDailyQ <- readNWISdv(site_id,pCode, startDate, endDate)
rawDailyQAndTempMeanMax <- readNWISdv(site_id,c('00010','00060'),
  startDate, endDate, statCd=c('00001','00003'))
rawDailyQAndTempMeanMax <- renameNWISColumns(rawDailyQAndTempMeanMax)
rawDailyMultiSites<- readNWISdv(c("01491000","01645000"),c('00010','00060'),
  startDate, endDate, statCd=c('00001','00003'))
# Site with no data:
x <- readNWISdv("10258500","00060", "2014-09-08", "2014-09-14")
names(attributes(x))
attr(x, "siteInfo")
attr(x, "variableInfo")

site <- "05212700"
notActive <- readNWISdv(site, "00060", "2014-01-01","2014-01-07")

```

readNWISgw1

Groundwater level measurements retrieval from USGS (NWIS)

Description

Reads groundwater level measurements from NWISweb. Mixed date/times come back from the service depending on the year that the data was collected. See <https://waterdata.usgs.gov/usa/nwis/gw> for details about groundwater. By default the returned dates are converted to date objects, unless `convertType` is specified as `FALSE`. Sites with non-standard date formats (i.e. lacking a day) can be affected (see examples). See <https://waterservices.usgs.gov/rest/GW-Levels-Service.html> for more information.

Usage

```

readNWISgw1(
  siteNumbers,
  startDate = "",
  endDate = "",
  parameterCd = NA,
  convertType = TRUE,
  tz = "UTC"
)

```

Arguments

<code>siteNumbers</code>	character USGS site number (or multiple sites). This is usually an 8 digit number
<code>startDate</code>	character starting date for data retrieval in the form YYYY-MM-DD. Default is "" which indicates retrieval for the earliest possible record.

endDate	character ending date for data retrieval in the form YYYY-MM-DD. Default is "" which indicates retrieval for the latest possible record.
parameterCd	character USGS parameter code. This is usually an 5 digit number. Default is "".
convertType	logical, defaults to TRUE. If TRUE, the function will convert the data to dates, datetimes, numerics based on a standard algorithm. If false, everything is returned as a character
tz	character to set timezone attribute of dateTime. Default is "UTC", and converts the date times to UTC, properly accounting for daylight savings times based on the data's provided tz_cd column. Possible values to provide are "America/New_York", "America/Chicago", "America/Denver", "America/Los_Angeles", "America/Anchorage", as well as the following which do not use daylight savings time: "America/Honolulu", "America/Jamaica", "America/Managua", "America/Phoenix", and "America/Metlakatla". See also OlsonNames() for more information on time zones.

Value

A data frame with the following columns:

Name	Type	Description
agency_cd	character	The NWIS code for the agency reporting the data
site_no	character	The USGS site number
site_tp_cd	character	Site type code
lev_dt	Date	Date level measured
lev_tm	character	Time level measured
lev_tz_cd	character	Time datum
lev_va	numeric	Water level value in feet below land surface
sl_lev_va	numeric	Water level value in feet above specific vertical datum
lev_status_cd	character	The status of the site at the time the water level was measured
lev_agency_cd	character	The agency code of the person measuring the water level

There are also several useful attributes attached to the data frame:

Name	Type	Description
url	character	The url used to generate the data
queryTime	POSIXct	The time the data was returned
comment	character	Header comments from the RDB file
siteInfo	data.frame	A data frame containing information on the requested sites

See Also

[constructNWISURL](#), [importRDB1](#)

Examples

```

site_id <- "434400121275801"

data <- readNWISgwl(site_id)
sites <- c("434400121275801", "375907091432201")
data2 <- readNWISgwl(site_id, '', '')
data3 <- readNWISgwl("420125073193001", '', '')
#handling of data where date has no day
data4 <- readNWISgwl("425957088141001", startDate = "1980-01-01")

data5 <- readNWISgwl("263819081585801", parameterCd = "72019")

```

readNWISmeas

Surface-water measurement data retrieval from USGS (NWIS)

Description

Reads surface-water measurement data from NWISweb. Data is retrieved from <https://waterdata.usgs.gov/nwis>. See <https://waterdata.usgs.gov/usa/nwis/sw> for details about surface water.

Usage

```

readNWISmeas(
  siteNumbers,
  startDate = "",
  endDate = "",
  tz = "UTC",
  expanded = FALSE,
  convertType = TRUE
)

```

Arguments

siteNumbers	character USGS site number (or multiple sites). This is usually an 8 digit number
startDate	character starting date for data retrieval in the form YYYY-MM-DD. Default is "" which indicates retrieval for the earliest possible record.
endDate	character ending date for data retrieval in the form YYYY-MM-DD. Default is "" which indicates retrieval for the latest possible record.
tz	character to set timezone attribute of dateTime. Default is "UTC", and converts the date times to UTC, properly accounting for daylight savings times based on the data's provided tz_cd column. Possible values to provide are "America/New_York", "America/Chicago", "America/Denver", "America/Los_Angeles",

"America/Anchorage", as well as the following which do not use daylight savings time: "America/Honolulu", "America/Jamaica", "America/Managua", "America/Phoenix", and "America/Metlakatla". See also `OlsonNames()` for more information on time zones.

expanded	logical. Whether or not (TRUE or FALSE) to call the expanded data.
convertType	logical, defaults to TRUE. If TRUE, the function will convert the data to dates, datetimes, numerics based on a standard algorithm. If false, everything is returned as a character

Value

A data frame with at least the following columns:

Name	Type	Description
agency_cd	character	The NWIS code for the agency reporting the data
site_no	character	The USGS site number
measurement_dt	POSIXct	The date and time (in POSIXct) of the measurement. Unless specified with the tz parameter, the
tz_cd	character	The time zone code for the measurement_dt column

See <https://waterdata.usgs.gov/usa/nwis/sw> for details about surface water, and https://waterdata.usgs.gov/nwis/help?output_formats_help for help on the columns and codes.

There are also several useful attributes attached to the data frame:

Name	Type	Description
url	character	The url used to generate the data
queryTime	POSIXct	The time the data was returned
comment	character	Header comments from the RDB file
siteInfo	data.frame	A data frame containing information on the requested sites
tz_cd_reported		The originally reported time zone

See Also

[constructNWISURL](#), [importRDB1](#)

Examples

```
site_ids <- c('01594440', '040851325')

data <- readNWISmeas(site_ids)
Meas05316840 <- readNWISmeas("05316840")
Meas05316840.ex <- readNWISmeas("05316840", expanded=TRUE)
Meas07227500.ex <- readNWISmeas("07227500", expanded=TRUE)
Meas07227500.exRaw <- readNWISmeas("07227500", expanded=TRUE, convertType = FALSE)
```

readNWISpCode *USGS Parameter Data Retrieval*

Description

Imports data from NWIS about measured parameter based on user-supplied parameter code or codes. This function gets the data from here: <https://nwis.waterdata.usgs.gov/nwis/pmcodes>

Usage

```
readNWISpCode(parameterCd)
```

Arguments

parameterCd character of USGS parameter codes (or multiple parameter codes). These are 5 digit number codes, more information can be found here: <https://help.waterdata.usgs.gov/>. To get a complete list of all current parameter codes in the USGS, use "all" as the input.

Value

parameterData data frame with the following information:

Name	Type	Description
parameter_cd	character	5-digit USGS parameter code
parameter_group_nm	character	USGS parameter group name
parameter_nm	character	USGS parameter name
casrn	character	Chemical Abstracts Service (CAS) Registry Number
srsname	character	Substance Registry Services Name
parameter_units	character	Parameter units

See Also

[importRDB1](#)

Examples

```
paramINFO <- readNWISpCode(c('01075', '00060', '00931'))
paramINFO <- readNWISpCode(c('01075', '00060', '00931', NA))

all_codes <- readNWISpCode("all")
```

readNWISpeak	<i>Peak flow data from USGS (NWIS)</i>
--------------	--

Description

Reads peak flow from NWISweb. Data is retrieved from <https://waterdata.usgs.gov/nwis>. In some cases, the specific date of the peak data is not know. This function will default to converting complete dates to a "Date" object, and converting incomplete dates to "NA". If those incomplete dates are needed, set the 'asDateTime' argument to FALSE. No dates will be converted to R Date objects.

Usage

```
readNWISpeak(
  siteNumbers,
  startDate = "",
  endDate = "",
  asDateTime = TRUE,
  convertType = TRUE
)
```

Arguments

siteNumbers	character USGS site number(or multiple sites). This is usually an 8 digit number.
startDate	character starting date for data retrieval in the form YYYY-MM-DD. Default is "" which indicates retrieval for the earliest possible record.
endDate	character ending date for data retrieval in the form YYYY-MM-DD. Default is "" which indicates retrieval for the latest possible record.
asDateTime	logical default to TRUE. When TRUE, the peak_dt column is converted to a Date object, and incomplete dates are removed. When FALSE, no columns are removed, but no dates are converted.
convertType	logical, defaults to TRUE. If TRUE, the function will convert the data to dates, datetimes, numerics based on a standard algorithm. If false, everything is returned as a character

Value

A data frame with the following columns:

Name	Type	Description
agency_cd	character	The NWIS code for the agency reporting the data
site_no	character	The USGS site number
peak_dt	Date	Date of peak streamflow
peak_tm	character	Time of peak streamflow as character
peak_va	numeric	Annual peak streamflow value in cfs
peak_cd	character	Peak Discharge-Qualification codes (see comment for more information)

gage_ht	numeric	Gage height for the associated peak streamflow in feet
gage_ht_cd	character	Gage height qualification codes
year_last_pk	numeric	Peak streamflow reported is the highest since this year
ag_dt	Date	Date of maximum gage-height for water year (if not concurrent with peak)
ag_tm	character	Time of maximum gage-height for water year (if not concurrent with peak)
ag_gage_ht	numeric	maximum Gage height for water year in feet (if not concurrent with peak)
ag_gage_ht_cd	character	maximum Gage height code

There are also several useful attributes attached to the data frame:

Name	Type	Description
url	character	The url used to generate the data
queryTime	POSIXct	The time the data was returned
comment	character	Header comments from the RDB file
siteInfo	data.frame	A data frame containing information on the requested sites

See Also

[constructNWISURL](#), [importRDB1](#)

Examples

```
site_ids <- c('01594440', '040851325')

data <- readNWISpeak(site_ids)
data2 <- readNWISpeak(site_ids, asDateTime=FALSE)
stations<-c("06011000")
peakdata<-readNWISpeak(stations,convertType=FALSE)
```

readNWISqw

Raw Data Import for USGS NWIS QW Data

Description

Imports data from NWIS web service. This function gets the data from here: <https://nwis.waterdata.usgs.gov/nwis/qwdata> A list of parameter codes can be found here: <https://nwis.waterdata.usgs.gov/nwis/pmcodes/> A list of statistic codes can be found here: https://nwis.waterdata.usgs.gov/nwis/help/?read_file=stat&format=table

Usage

```
readNWISqw(
  siteNumbers,
  parameterCd,
  startDate = "",
  endDate = "",
  expanded = TRUE,
  reshape = FALSE,
  tz = "UTC"
)
```

Arguments

siteNumbers	character of USGS site numbers. This is usually an 8 digit number
parameterCd	character that contains the code for a parameter group, or a character vector of 5-digit parameter codes. See Details .
startDate	character starting date for data retrieval in the form YYYY-MM-DD. Default is "" which indicates retrieval for the earliest possible record. Date arguments are always specified in local time.
endDate	character ending date for data retrieval in the form YYYY-MM-DD. Default is "" which indicates retrieval for the latest possible record. Date arguments are always specified in local time.
expanded	logical defaults to TRUE. If TRUE, retrieves additional information. Expanded data includes remark_cd (remark code), result_va (result value), val_qual_tx (result value qualifier code), meth_cd (method code), dqi_cd (data-quality indicator code), rpt_lev_va (reporting level), and rpt_lev_cd (reporting level type). If FALSE, only returns remark_cd (remark code) and result_va (result value). Expanded = FALSE will not give sufficient information for unbiased statistical analysis.
reshape	logical, reshape the expanded data. If TRUE, then return a wide data frame with all water-quality in a single row for each sample. If FALSE (default), then return a long data frame with each water-quality result in a single row. This argument is only applicable to expanded data. Data requested using expanded=FALSE is always returned in the wide format.
tz	character to set timezone attribute of dateTime. Default is "UTC", and converts the date times to UTC, properly accounting for daylight savings times based on the data's provided tz_cd column. Possible values to provide are "America/New_York", "America/Chicago", "America/Denver", "America/Los_Angeles", "America/Anchorage", as well as the following which do not use daylight savings time: "America/Honolulu", "America/Jamaica", "America/Managua", "America/Phoenix", and "America/Metlakatla". See also OlsonNames() for more information on time zones.

Details

Valid parameter code groups are "All," or group codes:

Code	Description
INF	Information
PHY	Physical
INM	Inorganics, Major, Metals
INN	Inorganics, Major, Non-metals
NUT	Nutrient
MBI	Microbiological
BIO	Biological
IMN	Inorganics, Minor, Non-metals
IMM	Inorganics, Minor, Metals
TOX	Toxicity
OPE	Organics, pesticide
OPC	Organics, PCBs
OOT	Organics, other
RAD	Radiochemistry
SED	Sediment
POP	Population/community
OTH	Other
HAB	Habitat
ISO	Stable Isotopes

If more than one parameter group is requested, only sites that data for all requested groups are returned.

Value

A data frame with at least the following columns:

Name	Type	Description
agency_cd	character	The NWIS code for the agency reporting the data
site_no	character	The USGS site number
sample_dt	Date	The date the sample was collected
sample_tm	character	The reported sample collection time
startDateTime	POSIXct	Combining sample_dt and sample_tm, a date/time column is created, and converted into UTC (UTC is preferred)
endDateTime	POSIXct	If any sample_end_dt and sample_end_tm exist, this column is created similar to startDateTime

Further columns will be included depending on the requested output format (expanded = TRUE or FALSE). Columns that end in "_reported" are the originally reported timezones, but the "tz_cd" column defines the timezone of any POSIXct columns.

There are also several useful attributes attached to the data frame:

Name	Type	Description
url	character	The url used to generate the data
queryTime	POSIXct	The time the data was returned
comment	character	Header comments from the RDB file
siteInfo	data frame	A data frame containing information on the requested sites

variableInfo data frame A data frame containing information on the requested parameters

See Also

[readWQPdata](#), [whatWQPsites](#), [readWQPqw](#), [constructNWISURL](#)

readNWISrating	<i>Rating table for an active USGS streamgage retrieval</i>
----------------	---

Description

Reads current rating table for an active USGS streamgage from NWISweb. Data is retrieved from <https://waterdata.usgs.gov/nwis>.

Usage

```
readNWISrating(siteNumber, type = "base", convertType = TRUE)
```

Arguments

siteNumber	character USGS site number. This is usually an 8 digit number
type	character can be "base", "corr", or "exsa"
convertType	logical, defaults to TRUE. If TRUE, the function will convert the data to dates, datetimes, numerics based on a standard algorithm. If false, everything is returned as a character

Value

A data frame. If type is "base," then the columns are INDEP, typically the gage height, in feet; DEP, typically the streamflow, in cubic feet per second; and STOR, where "*" indicates that the pair are a fixed point of the rating curve. If type is "exsa," then an additional column, SHIFT, is included that indicates the current shift in the rating for that value of INDEP. If type is "corr," then the columns are INDEP, typically the gage height, in feet; CORR, the correction for that value; and CORRINDEP, the corrected value for CORR.

If type is "base," then the data frame has an attribute called "RATING" that describes the rating curve is included.

There are also several useful attributes attached to the data frame:

Name	Type	Description
url	character	The url used to generate the data
queryTime	POSIXct	The time the data was returned
comment	character	Header comments from the RDB file
siteInfo	data.frame	A data frame containing information on the requested sites
RATING	character	Rating information

Note

Not all active USGS streamgages have traditional rating curves that relate flow to stage.

See Also

[constructNWISURL](#), [importRDB1](#)

Examples

```
site_id <- '01594440'

data <- readNWISrating(site_id, "base")
attr(data, "RATING")
```

readNWISsite

USGS Site File Data Retrieval

Description

Imports data from USGS site file site. This function gets data from here: <https://waterservices.usgs.gov/>

Usage

```
readNWISsite(siteNumbers)
```

Arguments

siteNumbers character USGS site number (or multiple sites). This is usually an 8 digit number

Value

A data frame with at least the following columns:

Name	Type	Description
agency_cd	character	The NWIS code for the agency reporting the data
site_no	character	The USGS site number
station_nm	character	Site name
site_tp_cd	character	Site type
lat_va	numeric	DMS latitude
long_va	numeric	DMS longitude
dec_lat_va	numeric	Decimal latitude
dec_long_va	numeric	Decimal longitude
coord_meth_cd	character	Latitude-longitude method
coord_acy_cd	character	Latitude-longitude accuracy

coord_datum_cd	character	Latitude-longitude datum
dec_coord_datum_cd	character	Decimal Latitude-longitude datum
district_cd	character	District code
state_cd	character	State code
county_cd	character	County code
country_cd	character	Country code
land_net_ds	character	Land net location description
map_nm	character	Name of location map
map_scale_fc	character	Scale of location map
alt_va	numeric	Altitude of Gage/land surface
alt_meth_cd	character	Method altitude determined
alt_acy_va	numeric	Altitude accuracy
alt_datum_cd	character	Altitude datum
huc_cd	character	Hydrologic unit code
basin_cd	character	Drainage basin code
topo_cd	character	Topographic setting code
instruments_cd	character	Flags for instruments at site
construction_dt	character	Date of first construction
inventory_dt	character	Date site established or inventoried
drain_area_va	numeric	Drainage area
contrib_drain_area_va	numeric	Contributing drainage area
tz_cd	character	Time Zone abbreviation
local_time_fg	character	Site honors Daylight Savings Time
reliability_cd	character	Data reliability code
gw_file_cd	character	Data-other GW files
nat_aqfr_cd	character	National aquifer code
aqfr_cd	character	Local aquifer code
aqfr_type_cd	character	Local aquifer type code
well_depth_va	numeric	Well depth
hole_depth_va	numeric	Hole depth
depth_src_cd	character	Source of depth data
project_no	character	Project number

There are also several useful attributes attached to the data frame:

Name	Type	Description
url	character	The url used to generate the data
queryTime	POSIXct	The time the data was returned
comment	character	Header comments from the RDB file

Examples

```
siteINFO <- readNWISsite('05114000')
siteINFOMulti <- readNWISsite(c('05114000','09423350'))
```

readNWISstat	<i>Site statistics retrieval from USGS (NWIS)</i>
--------------	---

Description

Retrieves site statistics from the USGS Statistics Web Service beta. See <https://waterservices.usgs.gov/rest/Statistics-Service.html> for more information.

Usage

```
readNWISstat(
  siteNumbers,
  parameterCd,
  startDate = "",
  endDate = "",
  convertType = TRUE,
  statReportType = "daily",
  statType = "mean"
)
```

Arguments

siteNumbers	character USGS site number (or multiple sites). This is usually an 8 digit number.
parameterCd	character USGS parameter code. This is usually a 5 digit number.
startDate	character starting date for data retrieval in the form YYYY, YYYY-MM, or YYYY-MM-DD. Dates cannot be more specific than the statReportType, i.e. startDate for monthly statReportTypes cannot include days, and annual statReportTypes cannot include days or months. Months and days are optional for the daily statReportType. Default is "" which indicates retrieval for the earliest possible record. For daily data, this indicates the start of the period the statistics will be computed over.
endDate	character ending date for data retrieval in the form YYYY, YYYY-MM, or YYYY-MM-DD. Default is "" which indicates retrieval for the latest possible record. For daily data, this indicates the end of the period the statistics will be computed over. The same restrictions as startDate apply.
convertType	logical, defaults to TRUE. If TRUE, the function will convert the data to numerics based on a standard algorithm. Years, months, and days (if applicable) are also returned as numerics in separate columns. If convertType is false, everything is returned as a character.

- statReportType** character time division for statistics: daily, monthly, or annual. Default is daily. Note that daily provides statistics for each calendar day over the specified range of water years, i.e. no more than 366 data points will be returned for each site/parameter. Use `readNWISdata` or `readNWISdv` for daily averages. Also note that 'annual' returns statistics for the calendar year. Use `readNWISdata` for water years. Monthly and yearly provide statistics for each month and year within the range individually.
- statType** character type(s) of statistics to output for daily values. Default is mean, which is the only option for monthly and yearly report types. See the statistics service documentation at <https://waterservices.usgs.gov/rest/Statistics-Service.html> for a full list of codes.

Value

A data frame with the following columns:

Name	Type	Description
agency_cd	character	The NWIS code for the agency report
site_no	character	The USGS site number
parameter_cd	character	The USGS parameter code

Other columns will be present depending on `statReportType` and `statType`

See Also

[constructNWISURL](#), [importRDB1](#)

Examples

```
x1 <- readNWISstat(siteNumbers=c("02319394"),
  parameterCd=c("00060"),
  statReportType="annual")

#all the annual mean discharge data for two sites
x2 <- readNWISstat(siteNumbers=c("02319394","02171500"),
  parameterCd=c("00010","00060"),
  statReportType="annual")

#Request p25, p75, and mean values for temperature and discharge for the 2000s
#Note that p25 and p75 were not available for temperature, and return NAs
x <- readNWISstat(siteNumbers=c("02171500"),
  parameterCd=c("00010","00060"),
  statReportType="daily",
  statType=c("mean","median"),
  startDate="2000",endDate="2010")
```

readNWISuse *Water use data retrieval from USGS (NWIS)*

Description

Retrieves water use data from USGS Water Use Data for the Nation. See <https://waterdata.usgs.gov/nwis/wu> for more information. All available use categories for the supplied arguments are retrieved.

Usage

```
readNWISuse(
  stateCd,
  countyCd,
  years = "ALL",
  categories = "ALL",
  convertType = TRUE,
  transform = FALSE
)
```

Arguments

stateCd	could be character (full name, abbreviation, id), or numeric (id). Only one is accepted per query.
countyCd	could be character (name, with or without "County", or "ALL"), numeric (id), or codeNULL, which will return state or national data depending on the stateCd argument. ALL may also be supplied, which will return data for every county in a state. Can be a vector of counties in the same state.
years	integer Years for data retrieval. Must be years ending in 0 or 5. Default is all available years.
categories	character categories of water use. Defaults to ALL. Specific categories must be supplied as two- letter abbreviations as seen in the URL when using the NWIS water use web interface. Note that there are different codes for national and state level data.
convertType	logical defaults to TRUE. If TRUE, the function will convert the data to numerics based on a standard algorithm. Years, months, and days (if applicable) are also returned as numerics in separate columns. If convertType is false, everything is returned as a character.
transform	logical only intended for use with national data. Defaults to FALSE, with data being returned as presented by the web service. If TRUE, data will be transformed and returned with column names, which will reformat national data to be similar to state data.

Value

A data frame with at least the year of record, and all available statistics for the given geographic parameters. County and state fields will be included as appropriate.

Examples

```
#All data for a county
alleggheny <- readNWISuse(stateCd = "Pennsylvania",countyCd = "Allegheny")

#Data for an entire state for certain years
ohio <- readNWISuse(years=c(2000,2005,2010),stateCd = "OH", countyCd = NULL)

#Data for an entire state, county by county
pr <- readNWISuse(years=c(2000,2005,2010),stateCd = "PR",countyCd="ALL")

#All national-scale data, transforming data frame to named columns from named rows
national <- readNWISuse(stateCd = NULL, countyCd = NULL, transform = TRUE)

#Washington, DC data
dc <- readNWISuse(stateCd = "DC",countyCd = NULL)

#data for multiple counties, with different input formatting
paData <- readNWISuse(stateCd = "42",countyCd = c("Allegheny County", "BUTLER", 1, "031"))

#retrieving two specific categories for an entire state
ks <- readNWISuse(stateCd = "KS", countyCd = NULL, categories = c("IT","LI"))
```

readNWISuv

Instantaneous value data retrieval from USGS (NWIS)

Description

Imports data from NWIS web service. This function gets the data from here: <https://waterservices.usgs.gov/> A list of parameter codes can be found here: <https://nwis.waterdata.usgs.gov/nwis/pmcodes/> A list of statistic codes can be found here: https://nwis.waterdata.usgs.gov/nwis/help/?read_file=stat&format=table. More information on the web service can be found here: <https://waterservices.usgs.gov/rest/IV-Service.html>.

Usage

```
readNWISuv(siteNumbers, parameterCd, startDate = "", endDate = "", tz = "UTC")
```

Arguments

siteNumbers	character USGS site number (or multiple sites). This is usually an 8 digit number
parameterCd	character USGS parameter code. This is usually an 5 digit number.
startDate	character starting date for data retrieval in the form YYYY-MM-DD. Default is "" which indicates retrieval for the earliest possible record. Simple date arguments are specified in local time. See more information here: https://waterservices.usgs.gov/rest/IV-Service.html .

endDate	character ending date for data retrieval in the form YYYY-MM-DD. Default is "" which indicates retrieval for the latest possible record. Simple date arguments are specified in local time. See more information here: https://waterservices.usgs.gov/rest/IV-Service.html .
tz	character to set timezone attribute of dateTime. Default is "UTC", and converts the date times to UTC, properly accounting for daylight savings times based on the data's provided tz_cd column. Possible values to provide are "America/New_York", "America/Chicago", "America/Denver", "America/Los_Angeles", "America/Anchorage", as well as the following which do not use daylight savings time: "America/Honolulu", "America/Jamaica", "America/Managua", "America/Phoenix", and "America/Metlakatla". See also OlsonNames() for more information on time zones.

Value

A data frame with the following columns:

Name	Type	Description
agency_cd	character	The NWIS code for the agency reporting the data
site_no	character	The USGS site number
dateTime	POSIXct	The date and time of the value converted to UTC
tz_cd	character	The time zone code for dateTime
code	character	Any codes that qualify the corresponding value
value	numeric	The numeric value for the parameter

Note that code and value are repeated for the parameters requested. The names are of the form: X_D_P_S, where X is literal, D is an option description of the parameter, P is the parameter code, and S is the statistic code (if applicable).

There are also several useful attributes attached to the data frame:

Name	Type	Description
url	character	The url used to generate the data
siteInfo	data.frame	A data frame containing information on the requested sites
variableInfo	data.frame	A data frame containing information on the requested parameters
statisticInfo	data.frame	A data frame containing information on the requested statistics on the data
queryTime	POSIXct	The time the data was returned

See Also

[renameNWISColumns](#), [importWaterML1](#)

Examples

```
site_id <- '05114000'
parameterCd <- '00060'
```

```

startDate <- "2014-10-10"
endDate <- "2014-10-10"

rawData <- readNWISuv(site_id,parameterCd,startDate,endDate)

rawData_today <- readNWISuv(site_id, parameterCd, Sys.Date(),Sys.Date())

timeZoneChange <- readNWISuv(c('04024430','04024000'),parameterCd,
                             "2013-11-03","2013-11-03")

centralTime <- readNWISuv(site_id,parameterCd,
                          "2014-10-10T12:00", "2014-10-10T23:59",
                          tz="America/Chicago")

# Adding 'Z' to the time indicates to the web service to call the data with UTC time:
GMTdata <- readNWISuv(site_id,parameterCd,
                      "2014-10-10T00:00Z", "2014-10-10T23:59Z")

```

readWQPdata

General Data Import from Water Quality Portal

Description

Imports data from Water Quality Portal web service. This function gets the data from here: <https://www.waterqualitydata.us>. because it allows for other agencies rather than the USGS.

Usage

```
readWQPdata(..., querySummary = FALSE, tz = "UTC", ignore_attributes = FALSE)
```

Arguments

...	see https://www.waterqualitydata.us/webservices_documentation for a complete list of options. A list of arguments can also be supplied.
querySummary	logical to ONLY return the number of records and unique sites that will be returned from this query. This argument is not supported via the combined list from the ... argument
tz	character to set timezone attribute of dateTime. Default is "UTC", and converts the date times to UTC, properly accounting for daylight savings times based on the data's provided tz_cd column. Possible values to provide are "America/New_York","America/Chicago", "America/Denver","America/Los_Angeles", "America/Anchorage", as well as the following which do not use daylight savings time: "America/Honolulu", "America/Jamaica","America/Managua","America/Phoenix", and "America/Metlakatla". See also OlsonNames() for more information on time zones.

ignore_attributes

logical to choose to ignore fetching site and parameter attributes. Default is FALSE.

Value

A data frame with at least the following columns:

Name	Type	Description
OrganizationIdentifier	character	A designator used to uniquely identify a unique business.
OrganizationFormalName	character	The legal designator (i.e. formal name) of an organization.
ActivityIdentifier	character	Designator that uniquely identifies an activity within an organization.
ActivityTypeCode	character	The text describing the type of activity.
ActivityMediaName	character	Name or code indicating the environmental medium where the activity is conducted.
ActivityMediaSubdivisionName	character	Name or code indicating the environmental matrix as a subdivision of the medium.
ActivityStartDate	character	The calendar date on which the field activity is started.
ActivityStartTime.Time	character	The time of day that is reported when the field activity is started.
ActivityStartTime.TimeZoneCode	character	The time zone for which the time of day is reported.
ActivityEndDate	character	The calendar date when the field activity is completed.
ActivityEndTime.Time	character	The time of day that is reported when the field activity is completed.
ActivityEndTime.TimeZoneCode	character	The time zone for which the time of day is reported.
ActivityDepthHeightMeasure.MeasureValue	character	A measurement of the vertical location (measured from the datum or reference point).
ActivityDepthHeightMeasure.MeasureUnitCode	character	The code that represents the unit for measuring the item.
ActivityDepthAltitudeReferencePointText	character	The reference used to indicate the datum or reference point.
ActivityTopDepthHeightMeasure.MeasureValue	character	A measurement of the upper vertical location of a vertical measurement.
ActivityTopDepthHeightMeasure.MeasureUnitCode	character	The code that represents the unit for measuring the item.
ActivityBottomDepthHeightMeasure.MeasureValue	character	A measurement of the lower vertical location of a vertical measurement.
ActivityBottomDepthHeightMeasure.MeasureUnitCode	character	The code that represents the unit for measuring the item.
ProjectIdentifier	character	A designator used to uniquely identify a data collection project.
ActivityConductingOrganizationText	character	A name of the Organization conducting an activity.
MonitoringLocationIdentifier	character	A designator used to describe the unique name, number, or code of a monitoring location.
ActivityCommentText	character	General comments concerning the activity.
SampleAquifer *	character	A code that designates the aquifer associated with groundwater.
HydrologicCondition *	character	Hydrologic condition is the hydrologic condition that is associated with the sample.
HydrologicEvent *	character	A hydrologic event that is represented by the sample collection.
SampleCollectionMethod.MethodIdentifier	character	The identification number or code assigned by the method.
SampleCollectionMethod.MethodIdentifierContext	character	Identifies the source or data system that created or defined the method.
SampleCollectionMethod.MethodName	character	The title that appears on the method from the method procedure.
SampleCollectionEquipmentName	character	The name for the equipment used in collecting the sample.
ResultDetectionConditionText	character	The textual descriptor of a result.
CharacteristicName	character	The object, property, or substance which is evaluated or measured.
ResultSampleFractionText	character	The text name of the portion of the sample associated with the result.
ResultMeasureValue	numeric	The reportable measure of the result for the chemical, material, or parameter.
MeasureQualifierCode	character	A code used to identify any qualifying issues that affect the result.
ResultMeasure.MeasureUnitCode	character	The code that represents the unit for measuring the item.
ResultStatusIdentifier	character	Indicates the acceptability of the result with respect to the method.
StatisticalBaseCode	character	The code for the method used to calculate derived results.
ResultValueTypeName	character	A name that qualifies the process which was used in the result.
ResultWeightBasisText	character	The name that represents the form of the sample or portion.

ResultTimeBasisText	character	The period of time (in days) over which a measurement
ResultTemperatureBasisText	character	The name that represents the controlled temperature at
ResultParticleSizeBasisText	character	User defined free text describing the particle size class
PrecisionValue	character	A measure of mutual agreement among individual mea
ResultCommentText	character	Free text with general comments concerning the result.
USGSPCode *	character	5-digit number used in the US Geological Survey comp
ResultDepthHeightMeasure.MeasureValue +	character	A measurement of the vertical location (measured from
ResultDepthHeightMeasure.MeasureUnitCode +	character	The code that represents the unit for measuring the item
ResultDepthAltitudeReferencePointText +	character	The reference used to indicate the datum or reference u
SubjectTaxonomicName	character	The name of the organism from which a tissue sample
SampleTissueAnatomyName *	character	The name of the anatomy from which a tissue sample w
ResultAnalyticalMethod.MethodIdentifier	character	The identification number or code assigned by the meth
ResultAnalyticalMethod.MethodIdentifierContext	character	Identifies the source or data system that created or defin
ResultAnalyticalMethod.MethodName	character	The title that appears on the method from the method p
MethodDescriptionText *	character	A brief summary that provides general information abo
LaboratoryName	character	The name of Lab responsible for the result.
AnalysisStartDate	character	The calendar date on which the analysis began.
ResultLaboratoryCommentText	character	Remarks which further describe the laboratory procedu
DetectionQuantitationLimitTypeName	character	Text describing the type of detection or quantitation lev
DetectionQuantitationLimitMeasure.MeasureValue	numeric	Constituent concentration that, when processed throug
DetectionQuantitationLimitMeasure.MeasureUnitCode	character	The code that represents the unit for measuring the item
PreparationStartDate	character	The calendar date when the preparation/extraction of th
ActivityStartDateTime	POSIXct	Activity start date and time converted to POSIXct UTC
ActivityEndDateTime	POSIXct	Activity end date and time converted to POSIXct UTC.

* = elements only in NWIS + = elements only in STORET

There are also several useful attributes attached to the data frame:

Name	Type	Description
url	character	The url used to generate the data
siteInfo	data.frame	A data frame containing information on the requested sites
variableInfo	data.frame	A data frame containing information on the requested parameters
queryTime	POSIXct	The time the data was returned

Examples

```
nameToUse <- "pH"
pHData <- readWQPdata(siteid="USGS-04024315",characteristicName=nameToUse)
pHData_summary <- readWQPdata(bBox=c(-90.10,42.67,-88.64,43.35),
  characteristicName=nameToUse, querySummary=TRUE)
startDate <- as.Date("2013-01-01")
secchi.names = c("Depth, Secchi disk depth",
  "Depth, Secchi disk depth (choice list)",
  "Secchi Reading Condition (choice list)",
  "Water transparency, Secchi disc")
```



```

# Data profiles: "Sample Results (biological metadata)"
samp_bio <- readWQPdata(siteid="USGS-04024315",
                        dataProfile = "biological")

# Data profiles: "Sample Results (narrow)"
samp_narrow <- readWQPdata(siteid="USGS-04024315",
                           dataProfile = "narrowResult")

# Data profiles: "Sampling Activity"
samp_activity <- readWQPdata(siteid="USGS-04024315",
                              dataProfile = "activityAll")

# Data profile: "Sampling Activity Metrics"
act_metrics <- readWQPdata(statecode = "WI",
                           countycode = "Dane",
                           service = "ActivityMetric")

# Data profile: "Result Detection Quantitation Limit Data"
dl_data <- readWQPdata(siteid="USGS-04024315",
                       service = "ResultDetectionQuantitationLimit")

```

readWQPqw

Raw Data Import for Water Quality Portal

Description

Imports data from the Water Quality Portal. This function gets the data from here: <https://www.waterqualitydata.us>. There are four required input arguments: siteNumbers, parameterCd, startDate, and endDate. parameterCd can either be a USGS 5-digit code, or a characteristic name. The sites can be either USGS, or other Water Quality Portal offered sites. It is required to use the 'full' site name, such as 'USGS-01234567'.

Usage

```

readWQPqw(
  siteNumbers,
  parameterCd,
  startDate = "",
  endDate = "",
  tz = "UTC",
  querySummary = FALSE
)

```

Arguments

siteNumbers character site number. This needs to include the full agency code prefix.

parameterCd	vector of USGS 5-digit parameter code or characteristicNames. Leaving this blank will return all of the measured values during the specified time period.
startDate	character starting date for data retrieval in the form YYYY-MM-DD. Default is "" which indicates retrieval for the earliest possible record. Date arguments are always specified in local time.
endDate	character ending date for data retrieval in the form YYYY-MM-DD. Default is "" which indicates retrieval for the latest possible record. Date arguments are always specified in local time.
tz	character to set timezone attribute of dateTime. Default is "UTC", and converts the date times to UTC, properly accounting for daylight savings times based on the data's provided tz_cd column. Possible values to provide are "America/New_York", "America/Chicago", "America/Denver", "America/Los_Angeles", "America/Anchorage", as well as the following which do not use daylight savings time: "America/Honolulu", "America/Jamaica", "America/Managua", "America/Phoenix", and "America/Metlakatla". See also OlsonNames() for more information on time zones.
querySummary	logical to look at number of records and unique sites that will be returned from this query.

Value

A data frame with at least the following columns:

Name	Type	Description
OrganizationIdentifier	character	A designator used to uniquely identify a unique business.
OrganizationFormalName	character	The legal designator (i.e. formal name) of an organization.
ActivityIdentifier	character	Designator that uniquely identifies an activity within an organization.
ActivityTypeCode	character	The text describing the type of activity.
ActivityMediaName	character	Name or code indicating the environmental medium where the activity is conducted.
ActivityMediaSubdivisionName	character	Name or code indicating the environmental matrix as a subdivision of the medium.
ActivityStartDate	character	The calendar date on which the field activity is started.
ActivityStartTime.Time	character	The time of day that is reported when the field activity is started.
ActivityStartTime.TimeZoneCode	character	The time zone for which the time of day is reported.
ActivityEndDate	character	The calendar date when the field activity is completed.
ActivityEndTime.Time	character	The time of day that is reported when the field activity is completed.
ActivityEndTime.TimeZoneCode	character	The time zone for which the time of day is reported.
ActivityDepthHeightMeasure.MeasureValue	character	A measurement of the vertical location (measured from the datum or reference point).
ActivityDepthHeightMeasure.MeasureUnitCode	character	The code that represents the unit for measuring the item.
ActivityDepthAltitudeReferencePointText	character	The reference used to indicate the datum or reference point.
ActivityTopDepthHeightMeasure.MeasureValue	character	A measurement of the upper vertical location of a vertical measurement.
ActivityTopDepthHeightMeasure.MeasureUnitCode	character	The code that represents the unit for measuring the item.
ActivityBottomDepthHeightMeasure.MeasureValue	character	A measurement of the lower vertical location of a vertical measurement.
ActivityBottomDepthHeightMeasure.MeasureUnitCode	character	The code that represents the unit for measuring the item.
ProjectIdentifier	character	A designator used to uniquely identify a data collection project.
ActivityConductingOrganizationText	character	A name of the Organization conducting an activity.
MonitoringLocationIdentifier	character	A designator used to describe the unique name, number, or code of a monitoring location.
ActivityCommentText	character	General comments concerning the activity.
SampleAquifer *	character	A code that designates the aquifer associated with groundwater.

HydrologicCondition *	character	Hydrologic condition is the hydrologic condition that is
HydrologicEvent *	character	A hydrologic event that is represented by the sample co
SampleCollectionMethod.MethodIdentifier	character	The identification number or code assigned by the meth
SampleCollectionMethod.MethodIdentifierContext	character	Identifies the source or data system that created or defin
SampleCollectionMethod.MethodName	character	The title that appears on the method from the method p
SampleCollectionEquipmentName	character	The name for the equipment used in collecting the sam
ResultDetectionConditionText	character	The textual descriptor of a result.
CharacteristicName	character	The object, property, or substance which is evaluated o
ResultSampleFractionText	character	The text name of the portion of the sample associated w
ResultMeasureValue	numeric	The reportable measure of the result for the chemical, m
MeasureQualifierCode	character	A code used to identify any qualifying issues that affect
ResultMeasure.MeasureUnitCode	character	The code that represents the unit for measuring the item
ResultStatusIdentifier	character	Indicates the acceptability of the result with respect to
StatisticalBaseCode	character	The code for the method used to calculate derived resul
ResultValueTypeName	character	A name that qualifies the process which was used in the
ResultWeightBasisText	character	The name that represents the form of the sample or por
ResultTimeBasisText	character	The period of time (in days) over which a measurement
ResultTemperatureBasisText	character	The name that represents the controlled temperature at
ResultParticleSizeBasisText	character	User defined free text describing the particle size class
PrecisionValue	character	A measure of mutual agreement among individual mea
ResultCommentText	character	Free text with general comments concerning the result.
USGSPCode *	character	5-digit number used in the US Geological Survey comp
ResultDepthHeightMeasure.MeasureValue +	character	A measurement of the vertical location (measured from
ResultDepthHeightMeasure.MeasureUnitCode +	character	The code that represents the unit for measuring the item
ResultDepthAltitudeReferencePointText +	character	The reference used to indicate the datum or reference u
SubjectTaxonomicName	character	The name of the organism from which a tissue sample
SampleTissueAnatomyName *	character	The name of the anatomy from which a tissue sample w
ResultAnalyticalMethod.MethodIdentifier	character	The identification number or code assigned by the meth
ResultAnalyticalMethod.MethodIdentifierContext	character	Identifies the source or data system that created or defin
ResultAnalyticalMethod/MethodName	character	The title that appears on the method from the method p
MethodDescriptionText *	character	A brief summary that provides general information abo
LaboratoryName	character	The name of Lab responsible for the result.
AnalysisStartDate	character	The calendar date on which the analysis began.
ResultLaboratoryCommentText	character	Remarks which further describe the laboratory procedu
DetectionQuantitationLimitTypeName	character	Text describing the type of detection or quantitation lev
DetectionQuantitationLimitMeasure.MeasureValue	numeric	Constituent concentration that, when processed throug
DetectionQuantitationLimitMeasure.MeasureUnitCode	character	The code that represents the unit for measuring the item
PreparationStartDate	character	The calendar date when the preparation/extraction of th
ActivityStartDateTime	POSIXct	Activity start date and time converted to POSIXct UTC
ActivityEndDateTime	POSIXct	Activity end date and time converted to POSIXct UTC.

* = elements only in NWIS + = elements only in STORET

There are also several useful attributes attached to the data frame:

Name	Type	Description
url	character	The url used to generate the data
siteInfo	data.frame	A data frame containing information on the requested sites

variableInfo	data.frame	A data frame containing information on the requested parameters
queryTime	POSIXct	The time the data was returned

See Also

[readWQPdata](#), [whatWQPsites](#), [readNWISqw](#), and [importWQP](#)

Examples

```
rawPcode <- readWQPqw('USGS-01594440','01075', '', '')
rawCharacteristicName <- readWQPqw('WIDNR_WQX-10032762','Specific conductance', '', '')
rawPHsites <- readWQPqw(c('USGS-05406450', 'USGS-05427949', 'WIDNR_WQX-133040'), 'pH', '', '')
nwisEx <- readWQPqw('USGS-04024000', c('34247', '30234', '32104', '34220'), '', '2012-12-20')
nwisEx.summary <- readWQPqw('USGS-04024000', c('34247', '30234', '32104', '34220'),
  '', '2012-12-20', querySummary=TRUE)
```

readWQPsummary

Summary of Data Available from Water Quality Portal

Description

Returns a list of sites from the Water Quality Portal web service. This function gets the data from: <https://www.waterqualitydata.us>. Arguments to the function should be based on https://www.waterqualitydata.us/webservices_documentation. The information returned from this function describes the available data at the WQP sites, and some metadata on the sites themselves.

Usage

```
readWQPsummary(...)
```

Arguments

... see https://www.waterqualitydata.us/webservices_documentation for a complete list of options. A list of arguments can also be supplied.

Value

A data frame with at least the following columns:

Name	Type	Description
"Provider"	character	Providing database.
"MonitoringLocationIdentifier"	character	A designator used to describe the unique name, number, or code assigned to the site.
"YearSummarized"	numeric	The year of the summary

"CharacteristicType"	character	CharacteristicType
"CharacteristicName"	character	The object, property, or substance which is evaluated or enumerated
"ActivityCount"	numeric	The number of times the location was sampled
"ResultCount"	numeric	The number of individual data results.
"LastResultSubmittedDate"	Date	Date when data was last submitted.
"OrganizationIdentifier"	character	A designator used to uniquely identify a unique business establishment
"OrganizationFormalName"	character	The legal designator (i.e. formal name) of an organization.
"MonitoringLocationName"	character	MonitoringLocationName
"MonitoringLocationTypeName"	character	MonitoringLocationTypeName
"ResolvedMonitoringLocationTypeName"	character	
"HUCEightDigitCode"	character	8-digit HUC id.
"MonitoringLocationUrl"	character	URL to monitoring location.
"CountyName"	character	County of sampling location.
"StateName"	character	State of sampling location.
"MonitoringLocationLatitude"	numeric	latitude of sampling location.
"MonitoringLocationLongitude"	numeric	longitude of sampling location.

Examples

```
# Summary of a single site for the last 5 years:
site_5 <- readWQPsummary(siteid="USGS-07144100",
  summaryYears=5)

# Summary of a single site for the full period of record:
site_all <- readWQPsummary(siteid="USGS-07144100",
  summaryYears="all")

# Summary of the data available from streams in a single county:
dane_county_data <- readWQPsummary(countycode = "US:55:025",
  summaryYears = 5,
  siteType = "Stream")

# Summary of the data all available from lakes in a single county:
lake_sites <- readWQPsummary(siteType = "Lake, Reservoir, Impoundment",
  countycode = "US:55:025")

# Summary of the data available for the last 5 years in New Jersey:
state1 <- readWQPsummary(statecode="NJ",
  summaryYears = 5,
  siteType = "Stream")
```

Description

Rename columns coming back from NWIS data retrievals. Daily and unit value columns have names derived from their data descriptor, parameter, and statistic codes. This function reads information from the header and the arguments in the call to to rename those columns.

Usage

```
renameNWISColumns(
  rawData,
  p00010 = "Wtemp",
  p00045 = "Precip",
  p00060 = "Flow",
  p00065 = "GH",
  p00095 = "SpecCond",
  p00300 = "DO",
  p00400 = "pH",
  p62611 = "GWL",
  p63680 = "Turb",
  p72019 = "WLBSL",
  ...
)
```

Arguments

rawData	the daily- or unit-values dataset retrieved from NWISweb.
p00010	the base name for parameter code 00010.
p00045	the base name for parameter code 00045.
p00060	the base name for parameter code 00060.
p00065	the base name for parameter code 00065.
p00095	the base name for parameter code 00095.
p00300	the base name for parameter code 00300.
p00400	the base name for parameter code 00400.
p62611	the base name for parameter code 62611.
p63680	the base name for parameter code 63680.
p72019	the base name for parameter code 72019.
...	named arguments for the base name for any other parameter code. The form of the name must be like pXXXXX, where XXXXX is the parameter code.

Value

A dataset like data with selected columns renamed.

Note

The following statistics codes are converted by `renameNWISColumns`.

00000 Instantaneous Value, suffix: Inst
00001 Maximum value, suffix: Max
00002 Minimum value, suffix: Min
00003 Mean value, no suffix
00006 Sum of values, suffix: Sum
00007 Modal value, suffix: Mode
00008 Median value, suffix: Median
00012 Equivalent mean value, suffix: EqMean
00021 Tidal high-high value, suffix: HiHiTide
00022 Tidal low-high value, suffix: LoHiTide
00023 Tidal high-low value, suffix: HiLoTide
00024 Tidal low-low value, suffix: LoLoTide

See Also

[readNWISdv](#), [readNWISuv](#)

Examples

```
siteWithTwo <- '01480015'
startDate <- "2012-09-01"
endDate <- "2012-10-01"

twoResults <- readNWISdv(siteWithTwo, "00060", startDate, endDate)
names(twoResults)
renamedCols <- renameNWISColumns(twoResults)
names(renamedCols)
#Custom names:
newNames <- renameNWISColumns(twoResults, p00060="Discharge")
names(newNames)
```

setAccess

Set data endpoint

Description

access Indicate which dataRetrieval access code you want to use options: `c('public', 'internal')`

Usage

```
setAccess(access = "public")
```


Arguments

- access code for data access. Options are: "public", "internal", "cooperator", or "USGS".
- "internal" represents Access=3 ...for a single water science center
 - "USGS" represents Access=2 ...for all water science centers
 - "cooperator" represents Access=1
 - "public" represents Access=0, public access

Author(s)

Luke Winslow, Jordan S Read

Examples

```
setAccess('internal')
```

```
setAccess('public')
```

 stateCd

US State Code Lookup Table

Description

Data originally pulled from <https://www2.census.gov/geo/docs/reference/state.txt> on April 1, 2015. On Feb. 11, 2022, the fields were updated with the file found in inst/extdata, which is used internally with NWIS retrievals.

Value

stateCd data frame.

Name	Type	Description
STATE	character	FIPS State Code
STUSAB	character	Official United States Postal Service (USPS) Code
STATE_NAME	character	State Name
STATENS	character	Geographic Names Information System Identifier (GNISID)

Examples

```
head(stateCd)
```

stateCdLookup	<i>State code look up</i>
---------------	---------------------------

Description

Function to simplify finding state and state code definitions. Used in readNWISdata and readWQPdata.

Usage

```
stateCdLookup(input, outputType = "postal")
```

Arguments

input	could be character (full name, abbreviation, id), or numeric (id)
outputType	character can be "postal", "fullName", "tableIndex", or "id".

Examples

```
fullName <- stateCdLookup("wi", "fullName")
abbrev <- stateCdLookup("Wisconsin", "postal")
id <- stateCdLookup("WI", "id")
name <- stateCdLookup(55, "fullName")
index <- stateCdLookup("WI", "tableIndex")
stateCd[index,]
stateCdLookup(c("West Virginia", "Wisconsin", 200, 55, "MN"))
```

whatNWISdata	<i>USGS data availability</i>
--------------	-------------------------------

Description

Imports a table of available parameters, period of record, and count. See <https://waterservices.usgs.gov/rest/Site-Service.html> for more information.

Usage

```
whatNWISdata(..., convertType = TRUE)
```

Arguments

...	see https://waterservices.usgs.gov/rest/Site-Service.html for a complete list of options. A list of arguments can also be supplied.
convertType	logical, defaults to TRUE. If TRUE, the function will convert the data to dates, datetimes, numerics based on a standard algorithm. If false, everything is returned as a character

Value

A data frame with the following columns:

Name	Type	Description
agency_cd	character	The NWIS code for the agency reporting the data
site_no	character	The USGS site number
station_nm	character	Site name
site_tp_cd	character	Site type
dec_lat_va	numeric	Decimal latitude
dec_long_va	numeric	Decimal longitude
coord_acy_cd	character	Latitude-longitude accuracy
dec_coord_datum_cd	character	Decimal Latitude-longitude datum
alt_va	character	Altitude of Gage or land surface
alt_acy_va	character	Altitude accuracy
alt_datum_cd	character	Altitude datum
huc_cd	character	Hydrologic unit code
data_type_cd	character	Data type
parm_cd	character	Parameter code
stat_cd	character	Statistical code
dd_nu	character	Internal database key
loc_web_ds	character	Additional measurement description
medium_grp_cd	character	Medium group code
parm_grp_cd	character	Parameter group code
srs_id	character	SRS ID
access_cd	character	Access code
begin_date	Date	Begin date
end_date	Date	End date
count_nu	integer	Record count
parameter_group_nm	character	Parameter group name
parameter_nm	character	Parameter name
casrn	character	Chemical Abstracts Service (CAS) Registry Number
srsname	character	Substance Registry Services
parameter_units	character	Parameter units

There are also several useful attributes attached to the data frame:

Name	Type	Description
url	character	The url used to generate the data
comment	character	Header comments from the RDB file
queryTime	POSIXct	The time the data was returned

Examples

```

availableData <- whatNWISdata(siteNumber = '05114000')
# To find just unit value ('instantaneous') data:
uvData <- whatNWISdata(siteNumber = '05114000',service="uv")
uvDataMulti <- whatNWISdata(siteNumber = c('05114000','09423350'),service=c("uv","dv"))
flowAndTemp <- whatNWISdata(stateCd = "WI", service = "uv",
                             parameterCd = c("00060","00010"),
                             statCd = "00003")

```

 whatNWISsites

Site Data Import from NWIS

Description

Returns a list of sites from the NWIS web service. This function gets the data from: <https://waterservices.usgs.gov/rest/Site-Test-Tool.html>. Mapper format is used

Usage

```
whatNWISsites(...)
```

Arguments

... see <https://waterservices.usgs.gov/rest/Site-Service.html> for a complete list of options. A list (or lists) can also be supplied.

Value

A data frame with at least the following columns:

Name	Type	Description
agency_cd	character	The NWIS code for the agency reporting the data
site_no	character	The USGS site number
station_nm	character	Station name
site_tp_cd	character	Site type code
dec_lat_va	numeric	Decimal latitude
dec_long_va	numeric	Decimal longitude
queryTime	POSIXct	Query time

There are also several useful attributes attached to the data frame:

Name	Type	Description
url	character	The url used to generate the data
queryTime	POSIXct	The time the data was returned

Examples

```
sitelistPhos <- whatNWISsites(stateCd="OH",parameterCd="00665")
oneSite <- whatNWISsites(sites="05114000")
```

 whatWQPdata

Data Available from Water Quality Portal

Description

Returns a list of sites from the Water Quality Portal web service. This function gets the data from: <https://www.waterqualitydata.us>. Arguments to the function should be based on https://www.waterqualitydata.us/webservices_documentation. The information returned from this function describes the available data at the WQP sites, and some metadata on the sites themselves.

Usage

```
whatWQPdata(..., saveFile = tempfile())
```

Arguments

... see https://www.waterqualitydata.us/webservices_documentation for a complete list of options. A list of arguments can also be supplied.

saveFile path to save the incoming geojson output.

Value

A data frame with at least the following columns:

Name	Type	Description
"type_a"	character	Geojson type
"features.type"	character	Geojson feature type
"type1"	character	Geojson spatial type
"coordinates"	list	List of longitude/latitude
"ProviderName"	character	The name of the database that provided the data to the Water Quality Portal
"OrganizationIdentifier"	character	A designator used to uniquely identify a unique business establishment
"OrganizationFormalName"	character	The legal designator (i.e. formal name) of an organization.
"MonitoringLocationIdentifier"	character	A designator used to describe the unique name, number, or code assigned to a monitoring location.
"MonitoringLocationName"	character	The designator specified by the sampling organization for the site at the monitoring location.
"MonitoringLocationTypeName"	character	The descriptive name for a type of monitoring location.
"ResolvedMonitoringLocationTypeName"	character	The descriptive name for a type of monitoring location.
"HUCEightDigitCode"	character	The 8 digit federal code used to identify the hydrologic unit of the monitoring location.
"siteUrl"	character	URL to site information
"activityCount"	numeric	

"resultCount"	numeric	
"StateName"	character	State name
"CountyName"	character	County name

See Also

whatNWISSites

Examples

```
site1 <- whatWQPdata(siteid="USGS-01594440")

type <- "Stream"
sites <- whatWQPdata(countycode="US:55:025",siteType=type)

lakeSites <- whatWQPdata(siteType = "Lake, Reservoir, Impoundment", statecode = "US:55")
```

whatWQPsamples

Site Data Import from Water Quality Portal

Description

Returns a list of sites from the Water Quality Portal web service. This function gets the data from: <https://www.waterqualitydata.us>. Arguments to the function should be based on https://www.waterqualitydata.us/webservices_documentation. The return from this function returns the basic metadata on WQP sites. It is generally faster than the `whatWQPdata` function, but does not return information on what data was collected at the site.

Usage

```
whatWQPsamples(...)
```

```
whatWQPmetrics(...)
```

```
whatWQPsites(...)
```

Arguments

... see https://www.waterqualitydata.us/webservices_documentation for a complete list of options. A list of arguments can also be supplied.

Details

The `readWQPsummary` function has

Value

A data frame with at least the following columns:

Name	Type	Description
OrganizationIdentifier	character	A designator used to uniquely identify a unique business
OrganizationFormalName	character	The legal designator (i.e. formal name) of an organization
MonitoringLocationIdentifier	character	A designator used to describe the unique name, number
MonitoringLocationName	character	The designator specified by the sampling organization
MonitoringLocationTypeName	character	The descriptive name for a type of monitoring location
MonitoringLocationDescriptionText	character	Text description of the monitoring location.
HUCEightDigitCode	character	The 8 digit federal code used to identify the hydrologic
DrainageAreaMeasure/MeasureValue *	character	The drainage basin of a lake, stream, wetland, or estuarine
DrainageAreaMeasure/MeasureUnitCode *	character	The code that represents the unit for measuring the inter
ContributingDrainageAreaMeasure/MeasureValue *	character	The contributing drainage area of a lake, stream, wetland
ContributingDrainageAreaMeasure/MeasureUnitCode *	character	The code that represents the unit for measuring the inter
LatitudeMeasure	numeric	The measure of the angular distance on a meridian north
LongitudeMeasure	numeric	The measure of the angular distance on a meridian east
SourceMapScaleNumeric	character	The number that represents the proportional distance of
HorizontalAccuracyMeasure/MeasureValue *	character	The horizontal measure of the relative accuracy of the lat
HorizontalAccuracyMeasure/MeasureUnitCode *	character	The code that represents the unit for measuring the inter
HorizontalCollectionMethodName	character	The name that identifies the method used to determine
HorizontalCoordinateReferenceSystemDatumName	character	The name that describes the reference datum used in de
VerticalMeasure/MeasureValue	character	The measure of elevation (i.e., the altitude), above or be
VerticalMeasure/MeasureUnitCode	character	The code that represents the unit for measuring the inter
VerticalAccuracyMeasure/MeasureValue *	character	The vertical measure of the relative accuracy of the lati
VerticalAccuracyMeasure/MeasureUnitCode *	character	The code that represents the unit for measuring the inter
VerticalCollectionMethodName	character	The name that identifies the method used to collect the
VerticalCoordinateReferenceSystemDatumName	character	The name of the reference datum used to determine the
CountryCode	character	A code designator used to identify a primary geopolitic
StateCode	character	A code designator used to identify a principal administr
CountyCode	character	A code designator used to identify a U.S. county or cou
AquiferName *	character	Name of the aquifer in which the well is completed.
FormationTypeText *	character	Name of the primary formation or soils unit, in which t
AquiferTypeName *	character	The type of aquifer, such as confined or unconfined.
ConstructionDateText *	character	Date of construction when well was completed. May b
WellDepthMeasure/MeasureValue *	character	Depth below land surface datum (LSD) to the bottom o
WellDepthMeasure/MeasureUnitCode *	character	The code that represents the unit for measuring the inter
WellHoleDepthMeasure/MeasureValue *	character	Depth below land surface datum (LSD) to the bottom o
WellHoleDepthMeasure/MeasureUnitCode *	character	The code that represents the unit for measuring the inter
queryTime	POSIXct	Query time

* element is only in NWIS

See Also

whatNWISdata

Examples

```
site1 <- whatWQPsamples(siteid="USGS-01594440")

type <- "Stream"
sites <- whatWQPsamples(countycode="US:55:025",siteType=type)

type <- "Stream"
sites <- whatWQPmetrics(countycode="US:55:025",siteType=type)
lakeSites <- whatWQPmetrics(siteType = "Lake, Reservoir, Impoundment", statecode = "US:55")

site1 <- whatWQPsites(siteid="USGS-01594440")

type <- "Stream"
sites <- whatWQPsites(countycode="US:55:025",
                      characteristicName = "Phosphorus",
                      siteType=type)
```

zeroPad

Pad string with leading zeros

Description

Function to pad a string with leading zeros. Useful for parameter codes and USGS site IDs.

Usage

```
zeroPad(x, padTo)
```

Arguments

x	character
padTo	number Final desired length of the character

Value

x character returned with leading zeros

Examples

```
pCode <- '10'  
correctPCode <- zeroPad(pCode,5)  
pCodes <- c('100','1000','0','12345','1565465465465465')  
correctPCodes <- zeroPad(pCodes,5)  
pCodeNA <- c(1,2,NA)  
padPCodeNA <- zeroPad(pCodeNA,4)
```

Index

- * **IO**
 - renameNWISColumns, 54
- * **USGS**
 - constructNWISURL, 4
 - countyCd, 8
 - readNWISdv, 27
 - readNWISpCode, 33
 - readNWISqw, 35
 - readNWISsite, 39
 - readNWISuv, 44
 - readWQPqw, 50
 - stateCd, 57
 - whatNWISdata, 58
 - zeroPad, 64
- * **WQP**
 - constructWQPURL, 7
 - readWQPdata, 46
 - whatWQPdata, 61
 - whatWQPsamples, 62
- * **countyCd**
 - countyCd, 8
- * **data**
 - constructNWISURL, 4
 - constructWQPURL, 7
 - readNWISdv, 27
 - readNWISpCode, 33
 - readNWISqw, 35
 - readNWISsite, 39
 - readNWISuv, 44
 - readWQPdata, 46
 - readWQPqw, 50
 - whatNWISdata, 58
 - whatWQPdata, 61
 - whatWQPsamples, 62
 - zeroPad, 64
- * **import**
 - constructNWISURL, 4
 - constructWQPURL, 7
 - readNWISdv, 27
 - readNWISpCode, 33
 - readNWISqw, 35
 - readNWISsite, 39
 - readNWISuv, 44
 - readNWISpCode, 33
 - readNWISqw, 35
 - readNWISsite, 39
 - readNWISuv, 44
 - readWQPdata, 46
 - readWQPqw, 50
 - whatNWISdata, 58
 - whatWQPdata, 61
 - whatWQPsamples, 62
 - zeroPad, 64
- * **manip**
 - renameNWISColumns, 54
- * **nldi**
 - findNLDI, 9
 - get_nldi_sources, 13
- * **service**
 - constructNWISURL, 4
 - constructWQPURL, 7
 - readNWISdv, 27
 - readNWISpCode, 33
 - readNWISqw, 35
 - readNWISsite, 39
 - readNWISuv, 44
 - readWQPdata, 46
 - readWQPqw, 50
 - whatNWISdata, 58
 - whatWQPdata, 61
 - whatWQPsamples, 62
 - zeroPad, 64
- * **stateCd**
 - stateCd, 57
- * **web**
 - constructNWISURL, 4
 - constructWQPURL, 7
 - readNWISdv, 27
 - readNWISpCode, 33
 - readNWISqw, 35
 - readNWISsite, 39
 - readNWISuv, 44

readWQPdata, 46
readWQPqw, 50
whatNWISdata, 58
whatWQPdata, 61
whatWQPsamples, 62
zeroPad, 64

addWaterYear, 3

calcWaterYear, 4
constructNWISURL, 4, 30, 32, 35, 38, 39, 42
constructUseURL, 6
constructWQPURL, 7
countyCd, 8
countyCdLookup, 8

dataRetrieval, 9

findNLDI, 9

GET, 12
get_nldi_sources, 13
getQuerySummary, 11
getWebServiceData, 12

importNGWMN, 13
importRDB1, 14, 26, 30, 32, 33, 35, 39, 42
importWaterML1, 16, 26, 28, 45
importWaterML2, 18
importWQP, 19, 53
is_dataRetrieval_user, 20

parameterCdFile, 21

readNGWMNdata, 21
readNGWMNlevels, 22
readNGWMNsites, 23
readNWISdata, 24
readNWISdv, 27, 56
readNWISgw1, 29
readNWISmeas, 31
readNWISpCode, 33
readNWISpeak, 34
readNWISqw, 35, 53
readNWISrating, 38
readNWISsite, 39
readNWISstat, 41
readNWISuse, 43
readNWISuv, 44, 56
readWQPdata, 20, 38, 46, 53
readWQPqw, 20, 38, 50
readWQPsummary, 53
renameNWISColumns, 17, 26, 28, 45, 54

setAccess, 56
stateCd, 57
stateCdLookup, 58

whatNWISdata, 58
whatNWISSites, 60
whatWQPdata, 61, 62
whatWQPmetrics (whatWQPsamples), 62
whatWQPsamples, 62
whatWQPsites, 20, 38, 53
whatWQPsites (whatWQPsamples), 62

zeroPad, 64