

# Package ‘tidyvpc’

October 27, 2022

**Type** Package

**Title** VPC Percentiles and Prediction Intervals

**Version** 1.4.0

**Date** 2022-10-25

**Description** Perform a Visual Predictive Check (VPC), while accounting for stratification, censoring, and prediction correction. Using piping from 'magrittr', the intuitive syntax gives users a flexible and powerful method to generate VPCs using both traditional binning and a new binless approach Jansen et al. (2018) <[doi:10.1002/psp4.12319](https://doi.org/10.1002/psp4.12319)> with Additive Quantile Regression (AQR) and Locally Estimated Scatterplot Smoothing (LOESS) prediction correction.

**URL** <https://github.com/certara/tidyvpc>

**BugReports** <https://github.com/certara/tidyvpc/issues>

**Depends** R (>= 3.5.0),

**Imports** data.table (>= 1.9.8), magrittr, quantreg (>= 5.51), rlang (>= 0.3.0), methods, mgcv, classInt, ggplot2, stats, fastDummies, utils

**Suggests** cluster, dplyr, KernSmooth, knitr, shiny, remotes, vpc, rmarkdown, testthat (>= 2.1.0)

**License** MIT + file LICENSE

**LazyData** true

**Encoding** UTF-8

**VignetteBuilder** knitr

**RoxygenNote** 7.1.2

**NeedsCompilation** no

**Author** Olivier Barriere [aut],  
Benjamin Rich [aut],  
James Craig [aut, cre],  
Samer Mouksassi [aut],  
Kris Jansen [ctb],  
Certara USA, Inc. [cph, fnd]

**Maintainer** James Craig <james.craig@certara.com>

**Repository** CRAN

**Date/Publication** 2022-10-27 20:20:02 UTC

## R topics documented:

bininfo . . . . .	2
binless . . . . .	3
binning . . . . .	6
binningfunctions . . . . .	8
censoring . . . . .	9
check_order . . . . .	10
generics . . . . .	11
nopredcorrect . . . . .	11
npde . . . . .	12
observed . . . . .	13
obs_cat_data . . . . .	14
obs_data . . . . .	15
plot.tidyvpcobj . . . . .	16
predcorrect . . . . .	17
print.tidyvpcobj . . . . .	18
simulated . . . . .	19
sim_cat_data . . . . .	20
sim_data . . . . .	20
stratify . . . . .	21
vpstats . . . . .	22
<b>Index</b>	<b>24</b>

---

bininfo	<i>Obtain information about the bins from a tidyvpcobj</i>
---------	--

---

### Description

Obtain information about the bins from a tidyvpcobj

### Usage

```
bininfo(o, ...)

## S3 method for class 'tidyvpcobj'
bininfo(o, by.strata = o$bin.by.strata, ...)
```

**Arguments**

<code>o</code>	An object.
<code>...</code>	Additional arguments.
<code>by.strata</code>	Should the calculations be done by strata? Defaults to what was specified when the binning was done.

**Value**

A ‘data.table’ containing the following columns:

- `nobs`: Number of observed data points in the bin
- `xmedian`: Median x-value of the observed data points in the bin
- `xmean`: Mean x-value of the observed data points in the bin
- `xmax`: Maximum x-value of the observed data points in the bin
- `xmin`: Minimum x-value of the observed data points in the bin
- `xmid`: Value halfway between ‘`xmin`’ and ‘`xmax`’. x-value of the observed data points in the bin
- `xleft`: Value halfway between the minimum x-value of the current bin and the maximum x-value of the previous bin to the left (for the left-most bin, it is the minimum x-value).
- `xright`: Value halfway between the maximum x-value of the current bin and the minimum x-value of the next bin to the right (for the right-most bin, it is the maximum x-value).
- `xcenter`: Value halfway between ‘`xleft`’ and ‘`xright`’.

In addition, if stratification was performed, the stratification columns will be included as well.

**Methods (by class)**

- `tidyvpcobj`: Method for `tidyvpcobj`.

---

binless

*Perform binless Visual Predictive Check (VPC)*

---

**Description**

Use this function in place of traditional binning methods to derive VPC. For continuous VPC, this is obtained using additive quantile regression (`quantreg::rqss()`) and LOESS for pcVPC. While for categorical VPC, this is obtained using a generalized additive model (`gam(family = "binomial")`).

**Usage**

```
binless(o, ...)

## S3 method for class 'tidyvpcobj'
binless(
  o,
  optimize = TRUE,
  optimization.interval = c(0, 7),
  loess.ypc = FALSE,
  lambda = NULL,
  span = NULL,
  sp = NULL,
  ...
)
```

**Arguments**

<code>o</code>	A <code>tidyvpcobj</code> .
<code>...</code>	Other arguments to include will be ignored.
<code>optimize</code>	Logical indicating whether smoothing parameters should be optimized using AIC.
<code>optimization.interval</code>	Numeric vector of length 2 specifying the min/max range of smoothing parameter for optimization. Only applicable if <code>optimize = TRUE</code> .
<code>loess.ypc</code>	Logical indicating LOESS prediction corrected VPC. Must first use <a href="#">predcorrect</a> , if specifying <code>loess.ypc = TRUE</code> . Only applicable to continuous VPC.
<code>lambda</code>	Numeric vector of length 3 specifying lambda values for each quantile. If stratified, specify a <code>data.frame</code> with given strata represented the column name, and value specified as a numeric vector of length 3. See below examples. Only applicable to continuous VPC with <code>optimize = FALSE</code> .
<code>span</code>	Numeric between 0,1 specifying smoothing parameter for LOESS prediction correction. Only applicable for continuous VPC with <code>loess.ypc = TRUE</code> and <code>optimize = FALSE</code> .
<code>sp</code>	List of smoothing parameters applied to <code>mgcv::gam()</code> . Elements of list must be in the same order as unique values of DV. If one or more stratification variables present, the order of <code>sp</code> should be specified as unique combination of strata + DV, in ascending order. See below examples. Only applicable for categorical VPC, if <code>optimize = FALSE</code> .

**Value**

For continuous VPC, updates `tidyvpcobj` with additive quantile regression fits for observed and simulated data for quantiles specified in the `qpred` argument of `vpstats()`. If the `optimize = TRUE` argument is specified, the resulting `tidyvpcobj` will contain optimized lambda values according to AIC. For prediction corrected VPC (pcVPC), specifying `loess.ypc = TRUE` will return optimized span value for LOESS smoothing. For categorical VPC, updates `tidyvpcobj` with fits obtained by `gam(family="binomial")` for observed and simulated data for each category of DV

(in each stratum if stratify defined). If optimize = TRUE argument is specified, the resulting tidyvpcobj wil contain optimized sp values according to AIC.

### See Also

[observed simulated censoring predcorrect stratify binning vpcstats](#)

### Examples

```
require(magrittr)
require(data.table)

obs_data <- obs_data[MDV == 0]
sim_data <- sim_data[MDV == 0]

vpc <- observed(obs_data, y = DV, x = TIME) %>%
  simulated(sim_data, y = DV) %>%
  binless() %>%
  vpcstats()

# Binless example with LOESS prediction correction
obs_data$PRED <- sim_data[REP == 1, PRED]

vpc <- observed(obs_data, y = DV, x = TIME) %>%
  simulated(sim_data, y = DV) %>%
  predcorrect(pred = PRED) %>%
  binless(optimize = TRUE, loess.ypc = TRUE) %>%
  vpcstats()

# Binless example with user specified lambda values stratified on
# "GENDER" with 2 levels ("M", "F"), 10%, 50%, 90% quantiles.

lambda_strat <- data.table(
  GENDER_M = c(3,5,2),
  GENDER_F = c(1,3,4)
)

vpc <- observed(obs_data, y = DV, x = TIME) %>%
  simulated(sim_data, y = DV) %>%
  stratify(~ GENDER) %>%
  binless(optimize = FALSE, lambda = lambda_strat) %>%
  vpcstats(qpred = c(0.1, 0.5, 0.9))

# Binless example for categorical DV with optimized smoothing
vpc <- observed(obs_cat_data, x = agemoths, yobs = zlencat) %>%
  simulated(sim_cat_data, ysim = DV) %>%
  stratify(~ Country_ID_code) %>%
  binless() %>%
  vpcstats(vpc.type = "cat", quantile.type = 6)
```

```

# Binless example for categorical DV with user specified sp values
user_sp <- list(
Country1_prob0 = 100,
Country1_prob1 = 3,
Country1_prob2 = 4,
Country2_prob0 = 90,
Country2_prob1 = 3,
Country2_prob2 = 4,
Country3_prob0 = 55,
Country3_prob1 = 3,
Country3_prob2 = 200)

vpc <- observed(obs_cat_data, x = agemoths, yobs = zlencat) %>%
  simulated(sim_cat_data, ysim = DV) %>%
  stratify(~ Country_ID_code) %>%
  binless(optimize = FALSE, sp = user_sp) %>%
  vpcstats(vpc.type = "categorical", conf.level = 0.9, quantile.type = 6)

```

---

binning

*Binning methods for Visual Predictive Check (VPC)*


---

## Description

This function executes binning methods available in `classInt` i.e. "jenks", "kmeans", "sd", "pretty", "pam", "kmeans", "hclust", "bclust", "fisher", and "dph". You may also bin directly on x-variable or alternatively specify "centers" or "breaks". For explanation of binning methods see [classIntervals](#).

## Usage

```

binning(o, ...)

## S3 method for class 'tidyvpcobj'
binning(
  o,
  bin,
  data = o$data,
  xbin = "xmedian",
  centers,
  breaks,
  nbins,
  altx,
  stratum = NULL,
  by.strata = TRUE,
  ...
)

```

**Arguments**

<code>o</code>	A tidyvpcobj.
<code>...</code>	Other arguments to include for <code>classIntervals</code> . See <code>...</code> usage for style in <code>?classIntervals</code> .
<code>bin</code>	Character string indicating binning method or unquoted variable name if binning on x-variable.
<code>data</code>	Observed data supplied in <code>observed()</code> function.
<code>xbin</code>	Character string indicating midpoint type for binning.
<code>centers</code>	Numeric vector of centers for binning. Use <code>bin = "centers"</code> , if supplying centers.
<code>breaks</code>	Numeric vector of breaks for binning. Use <code>bin = "breaks"</code> , if supplying breaks.
<code>nbins</code>	Numeric number indicating the number of bins to use.
<code>altx</code>	Unquoted variable name in observed data for alternative x-variable binning.
<code>stratum</code>	List indicating the name of stratification variable and level, if using different binning methods by strata.
<code>by.strata</code>	Logical indicating whether binning should be performed by strata.

**Value**

Updates `tidyvpcobj` with `data.frame` containing bin information including left/right boundaries and midpoint, as specified in `xbin` argument.

**See Also**

[observed](#) [simulated](#) [censoring](#) [predcorrect](#) [stratify](#) [binless](#) [vpcstats](#)

**Examples**

```
require(magrittr)

# Binning on x-variable NTIME
vpc <- observed(obs_data, x=TIME, y=DV) %>%
  simulated(sim_data, y=DV) %>%
  binning(bin = NTIME) %>%
  vpcstats()

# Binning using ntile and xmean for midpoint
vpc <- observed(obs_data, x=TIME, y=DV) %>%
  simulated(sim_data, y=DV) %>%
  binning(bin = "ntile", nbins = 8, xbin = "xmean") %>%
  vpcstats()

# Binning using centers
vpc <- observed(obs_data, x=TIME, y=DV) %>%
  simulated(sim_data, y=DV) %>%
  binning(bin = "centers", centers = c(1,3,5,7)) %>%
```

```

vpcstats()

# Different Binning for each level of Strata
vpc <- observed(obs_data, x=TIME, y=DV) %>%
  simulated(sim_data, y=DV) %>%
  stratify(~ GENDER) %>%
  binning(stratum = list(GENDER = "M"), bin = "jenks", nbins = 5, by.strata = TRUE) %>%
  binning(stratum = list(GENDER = "F"), bin = "pam", nbins = 4, by.strata = TRUE) %>%
  vpcstats()

# Binning Categorical DV using rounded time variable

vpc <- observed(obs_cat_data, x = agemonths, y = zlencat ) %>%
  simulated(sim_cat_data, y = DV) %>%
  binning(bin = round(agemonths, 0)) %>%
  vpcstats(vpc.type = "categorical")

```

---

binningfunctions

*Different functions that perform binning.*


---

## Description

Different functions that perform binning.

## Usage

```

cut_at(breaks)

nearest(centers)

bin_by_ntile(nbins)

bin_by_eqcut(nbins)

bin_by_pam(nbins)

bin_by_classInt(style, nbins = NULL)

```

## Arguments

breaks	A numeric vector of values that designate cut points between bins.
centers	A numeric vector of values that designate the center of each bin.
nbins	The number of bins to split the data into.
style	a binning style (see <a href="#">classIntervals</a> for details).

**Value**

Each of these functions returns a function of a single numeric vector 'x' that assigns each value of 'x' to a bin.

**Examples**

```
x <- c(rnorm(10, 1, 1), rnorm(10, 3, 2), rnorm(20, 5, 3))
centers <- c(1, 3, 5)
nearest(centers)(x)

breaks <- c(2, 4)
cut_at(breaks)(x)

bin_by_eqcut(nbins=4)(x)
bin_by_ntile(nbins=4)(x)

bin_by_pam(nbins=4)(x)
bin_by_classInt("pretty", nbins=4)(x)
```

---

censoring

*Censoring observed data for Visual Predictive Check (VPC)*


---

**Description**

Specify censoring variable or censoring value for VPC.

**Usage**

```
censoring(o, ...)

## S3 method for class 'tidyvpcobj'
censoring(o, blq, lloq, alq, uloq, data = o$data, ...)
```

**Arguments**

o	A tidyvpcobj.
...	Other arguments to include.
blq	blq variable if present in observed data.
lloq	Numeric value or numeric variable in data indicating the upper limit of quantification.
alq	Logical variable indicating above limit of quantification.
uloq	Numeric value or numeric variable in data indicating the upper limit of quantification.
data	Observed data supplied in observed() function.

**Value**

Updates obs data.frame in tidypcobj with censored values for observed data which includes lloq and uloq specified values for lower/upper limit of quantification. Logicals for blq and alq are returned that indicate whether the DV value lies below/above limit of quantification.

**See Also**

[observed](#) [simulated](#) [stratify](#) [predcorrect](#) [binning](#) [binless](#) [vpcstats](#)

**Examples**

```
require(magrittr)

vpc <- observed(obs_data, x=TIME, y=DV) %>%
  simulated(sim_data, y=DV) %>%
  censoring(blq=(DV < 50), lloq=50) %>%
  binning(bin = "pam", nbins = 5) %>%
  vpcstats()

#Using LLOQ variable in data with different values of LLOQ by Study:

obs_data$LLOQ <- obs_data[, ifelse(STUDY == "Study A", 50, 25)]

vpc <- observed(obs_data, x=TIME, y=DV) %>%
  simulated(sim_data, y=DV) %>%
  censoring(blq=(DV < LLOQ), lloq=LLOQ) %>%
  stratify(~ STUDY) %>%
  binning(bin = "kmeans", nbins = 4) %>%
  vpcstats()
```

---

check\_order

*Perform a consistency check on observed and simulated data*

---

**Description**

This function performs a simple consistency check on an observed and simulated dataset to make sure they are consistent with respect to ordering as required by the other functions used in the VPC calculation.

**Usage**

```
check_order(obs, sim, tol = 1e-05)
```

**Arguments**

obs, sim	A 'data.frame' with 2 columns (see Details).
tol	A tolerance for comparing time values.

**Details**

The consistency check is performed by comparing a combination of unique subject identifier (ID) and time. Both `data.frame` objects must be given with those in positions 1 and 2, respectively.

**Value**

The number of replicates contained in 'sim'.

**See Also**

[observed](#), [simulated](#).

**Examples**

```
require(data.table)

check_order(obs_data[, .(ID, TIME)], sim_data[, .(ID, TIME)])
```

---

<code>generics</code>	<i>Perform a Visual Predictive Check (VPC) computation</i>
-----------------------	--

---

**Description**

These functions work together to calculate the statistics that are plotted in a VPC. They would typically be chained together using the "pipe" operator (see Examples).

**Arguments**

- `o`                    A `tidyvcobj`.
- `...`                Additional arguments.

---

<code>nopredcorrect</code>	<i>Remove prediction correction for Visual Predictive Check (VPC)</i>
----------------------------	---

---

**Description**

Optional function to use indicating no pred correction for VPC.

**Usage**

```

nopedcorrect(o, ...)

## S3 method for class 'tidyvcobj'
nopedcorrect(o, ...)

```

**Arguments**

```

o          A tidyvcobj.
...       Other arguments to include.

```

---

npde	<i>Normalized Prediction Distribution Errors</i>
------	--

---

**Description**

Normalized Prediction Distribution Errors

**Usage**

```

npde(o, ...)

## S3 method for class 'tidyvcobj'
npde(o, id, data = o$data, smooth = FALSE, ...)

```

**Arguments**

```

o          A tidyvcobj.
...       Additional arguments.
id        A vector of IDs. Used to associate observations (y) that originate from the same
          individual. Evaluated in the data.frame data.
data      A data.frame.
smooth    Should a uniform random perturbation be used to smooth the pd/pde values?

```

**References**

- Brendel, K., Comets, E., Laffont, C., Laveille, C. & Mentrée, F. Metrics for external model evaluation with an application to the population pharmacokinetics of gliclazide. *Pharm. Res.* (2006) 23(9), 2036–2049.
- Nguyen, T.H.T., et al. Model evaluation of continuous data pharmacometric models: metrics and graphics. *CPT Pharmacometrics Syst. Pharmacol.* (2017) 6(2), 87–109; doi:10.1002/psp4.12161.

**Examples**

```

require(magrittr)
require(ggplot2)

obs <- obs_data[MDV==0]
sim <- sim_data[MDV==0]

npde <- observed(obs, x=NULL, y=DV) %>%
  simulated(sim, y=DV) %>%
  npde(id=ID)

vpc <- observed(npde$npdeobs, x=epred, y=npde) %>%
  simulated(npde$npdesim, y=npde) %>%
  binning("eqcut", nbins=10) %>%
  vpcstats()

plot(vpc) +
  labs(x="Simulation-based Population Prediction", y="Normalized Prediction Distribution Error")

```

---

observed

*Specify observed dataset and variables for VPC*


---

**Description**

The observed function is the first function in the vpc piping chain and is used for specifying observed data and variables for VPC. Note: Observed data must not contain missing DV and may require filtering MDV == 0 before generating VPC.

**Usage**

```

observed(o, ...)

## S3 method for class 'data.frame'
observed(
  o,
  x,
  yobs,
  pred = NULL,
  blq = NULL,
  lloq = -Inf,
  alq = NULL,
  uloq = Inf,
  ...
)

```

**Arguments**

o	A data.frame of observation data.
...	Other arguments.
x	Numeric x-variable, typically named TIME.
yobs	Numeric y-variable, typically named DV.
pred	Population prediction variable, typically named PRED.
blq	Logical variable indicating below limit of quantification.
lloq	Number or numeric variable in data indicating the lower limit of quantification.
aloq	Logical variable indicating above limit of quantification .
uloq	Number or numeric variable in data indicating the upper limit of quantification.

**Value**

A tidyvpcobj containing both original data and observed data formatted with x and y variables as specified in function. Resulting data is of class data.frame and data.table.

**See Also**

[simulated censoring stratify predcorrect binning binless vpcstats](#)

**Examples**

```
obs_data <- obs_data[MDV == 0]
sim_data <- sim_data[MDV == 0]

vpc <- observed(obs_data, x=TIME, y=DV)
```

---

obs\_cat\_data

*Example observed data with categorical DV*

---

**Description**

An observed dataset with 3 levels of categorical DV.

**Usage**

```
obs_cat_data
```

**Format**

A data frame with 4014 rows and 4 variables:

**PID\_code** Subject identifier

**agemonths** Time

**zlencat** Categorical DV with the 3 levels

**Country\_ID\_code** Country code for stratification

**Source**

Certara University

---

obs\_data

*Example observed data with continuous DV*

---

**Description**

An observed dataset from a hypothetical PK model, altered to include NTIME, GROUP, GENDER.

**Usage**

obs\_data

**Format**

A data.table with 600 rows and 7 variables:

**ID** Subject identifier

**TIME** Time

**DV** Concentration of drug

**AMT** Amount of dosage initially administered at DV = 0, TIME = 0

**DOSE** Dosage amount

**MDV** Dummy indicating missing dependent variable value

**NTIME** Nominal Time

**GENDER** Character variable indicating subject's gender ("M", "F")

**STUDY** Character variable indicating study type ("Study A", "Study B")

**Source**

[simple\\_data](#)

---

```
plot.tidyvpcobj      Plot a tidyvpcobj
```

---

### Description

Use ggplot2 graphics to plot and customize the appearance of VPC.

### Usage

```
## S3 method for class 'tidyvpcobj'
plot(
  x,
  facet = FALSE,
  show.points = TRUE,
  show.boundaries = TRUE,
  show.stats = !is.null(x$stats),
  show.binning = isFALSE(show.stats),
  xlab = NULL,
  ylab = NULL,
  color = c("red", "blue", "red"),
  linetype = c("dotted", "solid", "dashed"),
  point.alpha = 0.4,
  point.size = 1,
  point.shape = "circle-fill",
  point.stroke = 1,
  ribbon.alpha = 0.1,
  legend.position = "top",
  facet.scales = "free",
  custom.theme = "ggplot2::theme_bw",
  ...
)
```

### Arguments

x	A tidyvpcobj.
facet	Set to TRUE to facet plot by quantile (continuous VPC) or category (categorical VPC).
show.points	Should the observed data points be plotted?
show.boundaries	Should the bin boundary be displayed?
show.stats	Should the VPC stats be displayed?
show.binning	Should the binning be displayed by coloring the observed data points by bin?
xlab	A character label for the x-axis.
ylab	A character label for the y-axis.
color	A character vector of colors for the percentiles, from low to high.

linetype	A character vector of line type for the percentiles, from low to high.
point.alpha	Numeric value specifying transparency of points.
point.size	Numeric value specifying size of point.
point.shape	Character one of "circle", "circle-fill", "diamond", "diamond-fill", "square", "square-fill", "triangle-fill", "triangle"). Defaults to "circle-fill".
point.stroke	Numeric value specifying size of point stroke.
ribbon.alpha	Numeric value specifying transparency of ribbon.
legend.position	A character string specifying the position of the legend. Options are "top", "bottom", "left", "right".
facet.scales	A character string specifying the scales argument to use for faceting. Options are "free", "fixed".
custom.theme	A character string specifying theme from ggplot2 package.
...	Further arguments can be specified but are ignored.

**Value**

A ggplot object.

**See Also**

ggplot

---

predcorrect	<i>Prediction corrected Visual Predictive Check (pcVPC)</i>
-------------	---

---

**Description**

Specify prediction variable for pcVPC.

**Usage**

```
predcorrect(o, ...)

## S3 method for class 'tidyvpcobj'
predcorrect(o, pred, data = o$data, ..., log = FALSE)
```

**Arguments**

o	A tidyvpcobj.
...	Other arguments to include.
pred	Prediction variable in observed data.
data	Observed data supplied in observed() function.
log	Logical indicating whether DV was modeled in logarithmic scale.

**Value**

Updates tidyvpcobj with required information to performing prediction correction, which includes the predcor logical indicating whether prediction corrected VPC is to be performed, the predcor.log logical indicating whether the DV is on a log-scale, and the pred prediction column from the original data.

**See Also**

[observed](#) [simulated](#) [censoring](#) [stratify](#) [binning](#) [binless](#) [vpcstats](#)

**Examples**

```
require(magrittr)

obs_data <- obs_data[MDV == 0]
sim_data <- sim_data[MDV == 0]

# Add PRED variable to observed data from first replicate of
# simulated data

obs_data$PRED <- sim_data[REP == 1, PRED]

vpc <- observed(obs_data, x=TIME, y=DV) %>%
  simulated(sim_data, y=DV) %>%
  binning(bin = NTIME) %>%
  predcorrect(pred=PRED) %>%
  vpcstats()

# For binless loess prediction corrected, use predcorrect() before
# binless() and set loess.ypc = TRUE

vpc <- observed(obs_data, x=TIME, y=DV) %>%
  simulated(sim_data, y=DV) %>%
  predcorrect(pred=PRED) %>%
  binless(loess.ypc = TRUE) %>%
  vpcstats()
```

---

```
print.tidyvpcobj
```

```
Print a tidyvpcobj
```

---

**Description**

Print generic used to return information about VPC.

**Usage**

```
## S3 method for class 'tidyvpobj'
print(x, ...)
```

**Arguments**

x                    An tidyvpobj.  
 ...                  Further arguments can be specified but are ignored.

**Value**

Returns x invisibly.

---

simulated	<i>Specify simulated dataset and variables for VPC</i>
-----------	--

---

**Description**

The simulated function is used for specifying simulated input data and variables for VPC. Note: Simulated data must not contain missing DV and may require filtering MDV == 0 before generating VPC. The ordering of observed and simulated data must also be consistent, with replicates in simulated data stacked on top of each other.

**Usage**

```
simulated(o, ...)

## S3 method for class 'tidyvpobj'
simulated(o, data, ysim, ...)
```

**Arguments**

o                    A tidyvpobj.  
 ...                  Other arguments.  
 data                A data.frame of simulated data.  
 ysim                Numeric y-variable, typically named DV.

**Value**

A tidyvpobj containing simulated dataset sim formatted with columns x, y, and repl, which indicates the replicate number. The column x is used from the observed() function. Resulting dataset is of class data.frame and data.table.

**See Also**

[observed censoring stratify predcorrect binning binless vpcstats](#)

**Examples**

```
require(magrittr)

vpc <- observed(obs_data, x=TIME, y=DV) %>%
  simulated(sim_data, y=DV)
```

---

sim_cat_data	<i>Example simulated data with categorical DV</i>
--------------	---

---

**Description**

A simulated dataset with the 3 levels of categorical DV across 100 replicates.

**Usage**

```
sim_cat_data
```

**Format**

A data frame with 401400 rows and 4 variables:

**PID\_code** Subject identifier

**IVAR** Time

**DV** Categorical DV with 3 levels

**Replicate** Replicate num for simulation

**Source**

Certara University

---

sim_data	<i>Example simulated data with continuous DV</i>
----------	--

---

**Description**

A simulated dataset from a hypothetical PK model with 100 replicates.

**Usage**

```
sim_data
```

**Format**

A data.table with 60000 rows and 10 variables:

**ID** Subject identifier

**REP** Replicate num for simulation

**TIME** Time

**DV** Concentration of drug

**IPRED** Individual prediction variable

**PRED** Population prediction variable

**AMT** Amount of dosage initially administered at DV = 0, TIME = 0

**DOSE** Dosage amount

**MDV** Dummy indicating missing dependent variable value

**NTIME** Nominal Time

**Source**

[simple\\_data](#)

---

stratify

*Stratification for Visual Predictive Check (VPC)*

---

**Description**

Use to specify stratification variables for VPC.

**Usage**

```
stratify(o, ...)
```

```
## S3 method for class 'tidyvpobj'
stratify(o, formula, data = o$data, ...)
```

**Arguments**

<code>o</code>	A tidyvpobj.
<code>...</code>	Other arguments to include.
<code>formula</code>	Formula for stratification.
<code>data</code>	Observed data supplied in observed() function.

**Value**

Returns updated tidyvpobj with stratification formula, stratification column(s), and strat.split datasets, which is obs split by unique levels of stratification variable(s). Resulting datasets are of class object data.frame and data.table.

**See Also**

[observed simulated censoring predcorrect binning binless vpcstats](#)

**Examples**

```
require(magrittr)

vpc <- observed(obs_data, x=TIME, y=DV) %>%
  simulated(sim_data, y=DV) %>%
  stratify(~ GENDER) %>%
  binning(NTIME) %>%
  vpcstats()

# Example with 2-way stratification by GENDER and STUDY.

vpc <- vpc %>%
  stratify(~ GENDER + STUDY) %>%
  binning(bin = "centers", centers = c(1,3,5,7,10)) %>%
  vpcstats()
```

---

vpcstats

*Compute VPC statistics*

---

**Description**

Compute prediction interval statistics for VPC.

**Usage**

```
vpcstats(o, ...)
```

```
## S3 method for class 'tidyvpcobj'
vpcstats(
  o,
  vpc.type = c("continuous", "categorical"),
  qpred = c(0.05, 0.5, 0.95),
  ...,
  conf.level = 0.95,
  quantile.type = 7
)
```

**Arguments**

<code>o</code>	A <code>tidyvpcobj</code> .
<code>...</code>	Other arguments to include.
<code>vpc.type</code>	Character specifying type of VPC (e.g., "continuous" (Default) or "categorical").

qpred	Numeric vector of length 3 specifying quantile prediction interval. Only applicable for <code>vpc.type = "continuous"</code> .
conf.level	Numeric specifying confidence level.
quantile.type	Numeric indicating quantile type. See <a href="#">quantile</a> .

**Value**

Updates `tidyvpcobj` with `stats` `data.table` object, which contains the following columns:

- `bin`: Resulting bin value as specified in `binning()` function
- `xbin`: Midpoint x-value of the observed data points in the bin as specified in `xbin` argument of `binning()` function
- `qname`: Quantiles specified in `qpred`. Only returned if `vpc.type = "continuous"`
- `pname`: Categorical probability names. Only returned if `vpc.type = "categorical"`
- `y`: Observed y value for the specified quantile
- `lo`: Lower bound of specified confidence interval for y value in simulated data
- `md`: Median y value in simulated data
- `hi`: Upper bound of specified confidence interval for y value in simulated data

**See Also**

[observed](#) [simulated](#) [censoring](#) [stratify](#) [binning](#) [binless](#) [predcorrect](#)

# Index

## \* datasets

- obs\_cat\_data, 14
- obs\_data, 15
- sim\_cat\_data, 20
- sim\_data, 20

- bin\_by\_classInt (binningfunctions), 8
- bin\_by\_eqcut (binningfunctions), 8
- bin\_by\_ntile (binningfunctions), 8
- bin\_by\_pam (binningfunctions), 8
- bininfo, 2
- binless, 3, 7, 10, 14, 18, 19, 22, 23
- binning, 5, 6, 10, 14, 18, 19, 22, 23
- binningfunctions, 8

- censoring, 5, 7, 9, 14, 18, 19, 22, 23
- check\_order, 10
- classIntervals, 6, 8
- cut\_at (binningfunctions), 8

- generics, 11

- nearest (binningfunctions), 8
- nopredcorrect, 11
- npde, 12

- obs\_cat\_data, 14
- obs\_data, 15
- observed, 5, 7, 10, 11, 13, 18, 19, 22, 23

- plot.tidyvpcobj, 16
- predcorrect, 4, 5, 7, 10, 14, 17, 19, 22, 23
- print.tidyvpcobj, 18

- quantile, 23

- sim\_cat\_data, 20
- sim\_data, 20
- simple\_data, 15, 21
- simulated, 5, 7, 10, 11, 14, 18, 19, 22, 23
- stratify, 5, 7, 10, 14, 18, 19, 21, 23
- vpstats, 5, 7, 10, 14, 18, 19, 22, 22